



REVISIONS		
REV.	DESCRIPTION	DATE
A	REDRAWN IN SW	1/20/2005

M12x1

WIRES TERMINATED VIA
SCREW TERMINALS

SPECIFICATIONS:	
RATED CURRENT (A)	2A
RATED VOLTAGE (V)	60V
MAX WIRE SIZE:	20AWG [0.5sqmm]
MIN WIRE SIZE:	24AWG [0.25sqmm]
CABLE GRIP RANGE:	.197 - .393" [5 - 10mm]
TEMP RATING:	-40°F - 185°F [-40°C - 85°C]
SEAL RATING:	IP 67

MATERIALS	
BODY:	POLYAMIDE
CONTACTS:	GOLD PLATED COPPER ALLOY
SEALS:	NBR
COUPLING:	NICKEL PLATED BRASS

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

SPECIFICATIONS	DO NOT SCALE DRAWING
----------------	----------------------

UNLESS OTHERWISE SPECIFIED:		NAME
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN	BEM
	CHECKED	
	ENG APPR.	
	MFG APPR.	
	Q.A.	
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE:		
8 POL MAL FIELD WIREABLE		
SIZE	DWG. NO.	REV
B	MDC-8MP-FW11	A
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1