		8	7	6	5	4		3		2	1	_
	PIN #	COLOR										
			_				Cut-Out					
D	1	WHITE										
	2	2 BROWN								1		D
	3	GREEN							[15.30 ∅.602			
									<i>♀</i> .002	-		
	4	YELLOW										
	5	GRAY	_						•			
	6	PINK	_						¥			
	7	BLUE										
	8	RED						[13.60]				
С					/Pg9			.535				С
C			L —		/ '9'	M12x1		/FLAT				C
⊸										TABLE A		_
						•				P/N	L	_
												-
						13.3			19.1	MDC-8MR-BM	12" [0.3M]	_
						.52			.75	MDC-8MR-BM-0.5M	20" [0.5M]	
						V				MDC-8MR-BM-0.6M	24" [0.6M]	
	MATERIALS								V	MDC-8MR-BM-1M	40" [1M]	В
	SHELL: CONTACTS:		(EL PLATED BRASS D PLATED COPPER ALLOY				KEY	WAY	<u>.</u>	MDC-8MR-BM-2M	79" [2M]	
	WIRES:		207/15/0							MDC-8MR-BM-3M	118" [3M]	
		STYLE: UL 1 AWG: 24 A			[20.1]					MDC-8MR-BM-4M	157" [4M]	
		JACKET: PVC		[2.2]			KELF	ATIVE TO FLAT $ ightarrow$				_
	V	OLTAGE: 300	1	.09	.79					MDC-8MR-BM-5M	197" [5M]	_
	INSERT:	-RING: NBR						UNLESS OTHERWISE SPECIFIED: DRAWN BY DIMENSIONS ARE IN INCHES DRAWN DATE		OTHER LENGTHS AVAILABLE CONSULT FACTORY		
	O-RING:											
	NUT:									MENCOM CORPO	DRATION	
	APPROVALS					AND [MM]			TITLE:		_	
Α	US: UL LISTED CANADA: C-UL LISTED							CHECK DATE				А
	ROHS:	YES			PROPRIETARY AND CONFIDENTIAL	VOLTS	60V					
	CE & UKCA:	: YES			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	AMPS	2A	MATERIAL		SIZE DWG. NO.	REV	-
					MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE			FINISH		B MDC-8MR-BM		
	RATINGS				WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS	TEMP:	105°C					
	PROTECTIO	N CLASS: UL T	YPE 4 & 12, IEC IP69		PROHIBITED.			DO NOT SCALE DRAWING		SCALE: 3:1 WEIGHT:	SHEET 1 OF 1	
		8	7	6	5	4		3		2	1	