



M12x1
FEMALE
THREAD

[20.8]
Ø.82

[62]
2.5

WIRES ARE TERMINATED VIA
SCREW TERMINALS

Voltage rating is 250V or the
rating of the cable, whichever
is less.

MATERIALS	
BODY:	NICKEL PLATED BRASS
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE SEAL:	NBR
INSERT:	POLYAMIDE
COUPLING:	NICKEL PLATED BRASS
RATINGS	
AMPS:	4A max
VOLTS:	250V max
SEAL:	IP67
CABLE RANGE:	18AWG - 24AWG
	0.118" - 0.354" (3mm - 9mm) OD

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	ADM
	DRAWN DATE	09/22/2016
	CHECKED BY	
	CHECK DATE	
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE:		
4 POLE MALE M12 FIELD WIREABLE CONNECTOR		
SIZE	DWG. NO.	REV
B	MDCM-4FP-FW	B
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1