	8	/	6	5	4		3		2		1
PIN#	COLOR										
1 E	BROWN										
	WHITE										
	BLUE										
4 E	BLACK										
-					L1 (R	Retracte	d)			I	
					L2 (E	Extende	d)				
					(7	[19]			
								0.75			
		12x1 MALE		[45]				-	7		
	TH			1.8		<u> </u>	R A		5] .20		
								φ	.20		
										<u> </u>	
							1 1				
b-		\mathcal{L}							Т		
>									T		
		[15]		[76]					[37]		
	_	[15] .6		[76] 3.0					[[37] 1.5		
MATERIAIS				[76] 3.0					1 5		
	YELLC	.6		[76] 3.0					1 5		
BODY:				[76] 3.0					1 5		
BODY: CONTACTS:		.6 OW PUR		[76] 3.0					1 5		
BODY: CONTACTS: CABLE:		OW PUR D PLATED COPPER ALLOY		[76] 3.0					1 5		
BODY: CONTACTS: CABLE:	STYLE: AWM AWG: 22/4	OW PUR D PLATED COPPER ALLOY		[76] 3.0				P/N	1 5		12
BODY: CONTACTS: CABLE: JA	STYLE: AWM AWG: 22/4 ACKET: YELLC	.6 OW PUR D PLATED COPPER ALLOY A OW PUR		[76] 3.0		₽		P/N MDCPQ	1.5	L1 21" [.53m]	L2 40" [1n
BODY: CONTACTS: CABLE: JA VOL	STYLE: AWM AWG: 22/4 ACKET: YELLC LTAGE: 300V	.6 OW PUR D PLATED COPPER ALLOY A OW PUR		[76] 3.0				MDCPQ	1.5 -4FP-1M	21" [.53m]	40" [1n
CONTACTS: CABLE: JA VOL	GOLI STYLE: AWM AWG: 22/4 ACKET: YELLC LTAGE: 300V SHIELD: NO	.6 OW PUR D PLATED COPPER ALLOY A OW PUR		[76] 3.0				MDCPQ	1.5		
BODY: CONTACTS: CABLE: JA VOL	STYLE: AWM AWG: 22/4 ACKET: YELLC LTAGE: 300V SHIELD: NO NICK	OW PUR D PLATED COPPER ALLOY A DW PUR		[76] 3.0				MDCPQ MDCPQ MDCPQ	1.5 -4FP-1M	21" [.53m]	40" [1n
BODY: CONTACTS: CABLE: JA VOL S COUPLING: INSERT:	STYLE: AWM AWG: 22/4 ACKET: YELLC LTAGE: 300V SHIELD: NO NICK	OW PUR D PLATED COPPER ALLOY A OW PUR CEL PLATED BRASS (AMIDE		[76] [3.0			UNLESS OTHERWISE SPECIF	MDCPQ MDCPQ MDCPQ IED: DRAWN BY ADM	-4FP-1M -4FP-2M -4FP-3.3M	21" [.53m] 29" [0.7m] 39" [1m]	40" [1n 79" [2n 120" [3.3
BODY: CONTACTS: CABLE: JA VOL S COUPLING: INSERT: O-RING:	STYLE: AWM AWG: 22/4 ACKET: YELLC LTAGE: 300V SHIELD: NO NICK POLY	OW PUR D PLATED COPPER ALLOY A OW PUR CEL PLATED BRASS (AMIDE		[76] 3.0			DIMENSIONS ARE IN INCHES	HED: DRAWN BY ADM	4FP-1M -4FP-2M -4FP-3.3M MENC	21" [.53m] 29" [0.7m]	40" [1n 79" [2n 120" [3.3
BODY: CONTACTS: CABLE: JA VOL S COUPLING: INSERT: O-RING: APPROVALS	GOLI STYLE: AWM AWG: 22/4 ACKET: YELLO LTAGE: 300V SHIELD: NO NICK POLY FPM	OW PUR D PLATED COPPER ALLOY A OW PUR CEL PLATED BRASS (AMIDE						Important Important <thimportant< th=""> <thimportant< th=""> <thi< td=""><td>-4FP-1M -4FP-2M -4FP-3.3M</td><td>21" [.53m] 29" [0.7m] 39" [1m]</td><td>40" [1n 79" [2n 120" [3.3</td></thi<></thimportant<></thimportant<>	-4FP-1M -4FP-2M -4FP-3.3M	21" [.53m] 29" [0.7m] 39" [1m]	40" [1n 79" [2n 120" [3.3
BODY: CONTACTS: CABLE: JA VOL S COUPLING: INSERT: O-RING: APPROVALS US:	GOLI STYLE: AWM AWG: 22/4 ACKET: YELLC LTAGE: 300V SHIELD: NO NICK POLY FPM	.6 OW PUR D PLATED COPPER ALLOY A OW PUR CEL PLATED BRASS (AMIDE					DIMENSIONS ARE IN INCHES	HED: DRAWN BY ADM	1.5 -4FP-1M -4FP-2M -4FP-3.3M MENC TITLE:	21" [.53m] 29" [0.7m] 39" [1m] COM CORP	40" [1n 79" [2i 120" [3.: ORATIO
BODY: CONTACTS: CABLE: JA VOL S COUPLING: INSERT: O-RING: APPROVALS US: CANADA:	GOLI STYLE: AWM AWG: 22/4 ACKET: YELLO LTAGE: 300V SHIELD: NO NICK POLY FPM UL LIS C-UL	OW PUR D PLATED COPPER ALLOY A OW PUR CEL PLATED BRASS (AMIDE				_	DIMENSIONS ARE IN INCHES	Important Important <thimportant< th=""> <thimportant< th=""> <thi< td=""><td>1.5 -4FP-1M -4FP-2M -4FP-3.3M MENC TITLE:</td><td>21" [.53m] 29" [0.7m] 39" [1m] COM CORP</td><td>40" [1n 79" [2i 120" [3.: ORATIO</td></thi<></thimportant<></thimportant<>	1.5 -4FP-1M -4FP-2M -4FP-3.3M MENC TITLE:	21" [.53m] 29" [0.7m] 39" [1m] COM CORP	40" [1n 79" [2i 120" [3.: ORATIO
BODY: CONTACTS: CABLE: JA VOL S COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS:	GOLI STYLE: AWM AWG: 22/4 ACKET: YELLO LTAGE: 300V SHIELD: NO NICK POLY FPM UL LIS C-UL YES	.6 OW PUR D PLATED COPPER ALLOY A OW PUR CEL PLATED BRASS (AMIDE		3.0	VOLTS	300V	DIMENSIONS ARE IN INCHES AND [MM]	Important Important <thimportant< th=""> <thimportant< th=""> <thi< td=""><td>1.5 4FP-1M 4FP-2M 4FP-3.3M MENC TITLE: 4 PL</td><td>21" [.53m] 29" [0.7m] 39" [1m] COM CORP COILED MI PLG</td><td>40" [1r 79" [2r 120" [3.: ORATIO</td></thi<></thimportant<></thimportant<>	1.5 4FP-1M 4FP-2M 4FP-3.3M MENC TITLE: 4 PL	21" [.53m] 29" [0.7m] 39" [1m] COM CORP COILED MI PLG	40" [1r 79" [2r 120" [3.: ORATIO
BODY: CONTACTS: CABLE: JA VOL S COUPLING: INSERT: O-RING: APPROVALS US: CANADA:	GOLI STYLE: AWM AWG: 22/4 ACKET: YELLO LTAGE: 300V SHIELD: NO NICK POLY FPM UL LIS C-UL	.6 OW PUR D PLATED COPPER ALLOY A OW PUR CEL PLATED BRASS (AMIDE		3.0 BROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	VOLTS AMPS	300V 4A	DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	Import Mathematical	1.5 -4FP-1M -4FP-2M -4FP-3.3M MENC TITLE: 4 PL SIZE DWG. N	21" [.53m] 29" [0.7m] 39" [1m] COM CORP COILED MI PLG	40" [1r 79" [2r 120" [3. ORATIO
BODY: CONTACTS: CABLE: JA VOL S COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS:	GOLI STYLE: AWM AWG: 22/4 ACKET: YELLO LTAGE: 300V SHIELD: NO NICK POLY FPM UL LIS C-UL YES	.6 OW PUR D PLATED COPPER ALLOY A OW PUR CEL PLATED BRASS (AMIDE		3.0 BROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS			DIMENSIONS ARE IN INCHES AND [MM]	Import Mathematical	1.5 -4FP-1M -4FP-2M -4FP-3.3M MENC TITLE: 4 PL SIZE DWG. N	21" [.53m] 29" [0.7m] 39" [1m] COM CORP COILED MI PLG	40" [1r 79" [2r 120" [3.3 ORATIO

