

P/N	L	STD?
MDCW-4MFP-0.5M	20" [0.5M]	YES
MDCW-4MFP-1M	40" [1M]	YES
MDCW-4MFP-2M	79" [2M]	YES
MDCW-4MFP-3M	118" [3M]	YES
MDCW-4MFP-4M	157" [4M]	YES
MDCW-4MFP-5M	197" [5M]	YES
MDCW-4MFP-6M	236" [6M]	NO
MDCW-4MFP-8M	315" [8M]	NO
MDCW-4MFP-10M	393" [10M]	YES
MDCW-4MFP-15M	590" [15M]	YES
MDCW-4MFP-20M	786" [20M]	NO
MDCW-4MFP-30M	1179" [30M]	NO

PARTS LISTED AS NOT BEING STANDARD MAY HAVE MINIMUM ORDER QUANTITIES

		MA	HAVE MINIM	UM ORDER QU	ANIIIIES	
UNLESS OTHERWISE SPECIFIED:	DRAWN BY	ADM	MENCOM CORPORATION			
DIMENSIONS ARE IN INCHES	DRAWN DATE	06/26/2023	MENCOM CORI ORAHON		J14	
AND [MM]	CHECKED BY	JJH	TITLE:			
	CHECK DATE	06/27/2023	4 POL M-F EXT, TPE			
MATERIAI	SCALE, 2,0 WEIGHT.		CITE DIMC NO		חבי	,
THE WELLOW				REV	′	
FINISH			B MDCW-4MFP-ZZ)
DO NOT SCALE DRAWING			SCALE: 3:2 WEIG	GHT:	SHEET 1 OF	1

MATERIALS BODY: YELLOW PVC **CONTACTS:** GOLD PLATED COPPER ALLOY CABLE: STYLE: AWM AWG: 22 AWG JACKET: YELLOW TPE VOLTAGE: 600V SHIELD: NO COUPLING: NICKEL PLATED BRASS INSERT: POLYAMIDE O-RING: FPM **APPROVALS** A US: **UL LISTED** C-UL LISTED CANADA: ROHS: YES CE & UKCA: YES **RATINGS** PROTECTION CLASS: UL TYPE 4 & 12, IEC IP69

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

5

PROPRIETARY AND CONFIDENTIAL

VOLTS 300V **AMPS** 4A TEMP: 105°C