



| | | | MDE45WB-4 | 20" [0.5M] NO | | NO | | |
|-----------|------------|------------|--|---------------|-----------------|-------------|----------|--|
| | | I | MDE45WB-4 | IMMP-1M | 40" [1N | / 1] | YES | |
| | | | MDE45WB-4 | MMP-1.5M | 59" [1.5 | M] | NO | |
| | | | MDE45WB-4 | IMMP-2M | 79" [2 N | /1] | YES | |
| | | | MDE45WB-4 | 118" [3 | М1 | NO | | |
| | | | MDE45WB-4 | 157" [4 | _ | NO | | |
| | | | MDE45WB-4 | 197" [5 | _ | YES | | |
| | | | MDE45WB-4 | 236" [6 | _ | NO | | |
| | | | MDE45WB-4 | 315" [8 | _ | NO | | |
| | | | MDE45WB-4 | | _ | | YES | |
| | | - | | | 393" [10 | | | |
| | | | MDE45WB-4 | | 591" [15 | _ | YES | |
| | | | MDE45WB-4 | IMMP-20M | 786" [20 | M] | NO | |
| | | | MDE45WB-4 | IMMP-25M | 983" [25 | SM] | NO | |
| | | I | MDE45WB-4 | IMMP-30M | 1179" [3 | 0М] | NO | |
| | | | PARTS LISTED AS NOT BEING STANDARD MAY HAVE MINIMUM ORDER QUANTITIES | | | | | |
| : | DRAWN BY | ADM | MENCOM CORPORATION | | | | | |
| | DRAWN DATE | 08/24/2023 | | | | | | |
| | CHECKED BY | JJH | TITLE: | | | | | |
| | CHECK DATE | 08/24/2023 | 4 POL D-CODED M-M EXT PLG | | | | | |
| | | | | | | | | |
| COMMENTS: | | | | | | | | |
| | | | SIZE DWG. NO. REV | | | | | |
| | | | B MDE45WB-4MMP-ZZ B | | | | | |
| | | | SCALE: 3:2 | WEIGHT: | | SHEE | T 1 OF 1 | |
| | | | | | | | | |

TABLE A

P/N

D

STD?

3

UNLESS OTHERWISE SPECIFIED: DRAWN BY

DIMENSIONS ARE IN INCHES

DO NOT SCALE DRAWING

3

AND [MM]

MATERIAL

300V

80°C

4A

VOLTS

AMPS

TEMP:

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

5

| | MATERIALS | |
|---|-------------------|--------------------------------|
| | BODY: | BLACK PVC |
| | CONTACTS: | GOLD PLATED COPPER ALLOY |
| | CABLE: | |
| | STYLE: | AWM CAT 5e |
| | AWG: | 24 AWG |
| | JACKET: | TEAL TPE |
| | VOLTAGE: | 600V |
| | SHIELD: | BRAIDED |
| 4 | FLEX CYCLES: | 1MM @ 10X CABLE OD, MIN RADIUS |
| | COUPLING: | NICKEL PLATED BRASS |
| | INSERT: | POLYAMIDE |
| | O-RING: | N/A |
| | | |
| | RATINGS | |
| | PROTECTION CLASS: | UL TYPE 4 & 12, IEC IP69 |
| | | |