		8	7	6		5	4		3		
	MDE45	COLOR	RJ45								
	PIN #		PIN#								
	1	WHITE w/ORANGE	1								
D	2	WHITE w/GREEN	3								
	3	ORANGE	2								
	4	GREEN	6								
	N/C	SHIELD	SHIELD								
	_										
			-		\	L					
		[15]		44	I	I	40				
С		.6		1.7			1.6				
							-				
		Jacasso	M12x	K I							
	d and a second								▞ᡌᢩᢄ᠆᠆ᡜᡀ		
	3				$\prec$ $\leftarrow$			Υ		Т	ABLE A
	4										/N
-	1 <b>1</b>				<u>≺</u> <					P	/ IN
-	و								12345678	P	/1
-	و	a constant of the second secon							12345678		
-	6	A CONTRACTOR OF A CONTRACTOR							12345678	M	IDE45WB
-	MATERIALS	A CONTRACTOR OF A CONTRACTOR A C							12345678	M	IDE45WB IDE45WB
B	MATERIALS BODY:	BLACK PVC							12345678	M	IDE45WB IDE45WB
B			OPPER ALLOY						12345678	M M	IDE45WB IDE45WB IDE45WB
B	BODY:	GOLD PLATED CC	OPPER ALLOY						12345678	M M M	IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS:	GOLD PLATED CC STYLE: AWM CAT 5e	OPPER ALLOY						12345678	M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS: CABLE:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG	OPPER ALLOY						12345678	M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS: CABLE:	GOLD PLATED CO STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE	OPPER ALLOY						12345678	M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
В	BODY: CONTACTS: CABLE:	GOLD PLATED CO STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V	OPPER ALLOY						12345678	M M M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS: CABLE: V(	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED							12345678	M M M M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS: CABLE: V(	GOLD PLATED CO STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL	LE OD, MIN RADIUS						12345678	M M M M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS: CABLE: V( FLEX COUPLING:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI	LE OD, MIN RADIUS						12345678	M M M M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS: CABLE: Vo FLEX COUPLING: INSERT:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI POLYAMIDE	LE OD, MIN RADIUS						12345678 UNLESS OTHERWISE SPECIFIED	M M M M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS: CABLE: V( FLEX COUPLING:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI	LE OD, MIN RADIUS						UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	M M M M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
B	BODY: CONTACTS: CABLE: Vo FLEX COUPLING: INSERT:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI POLYAMIDE N/A	LE OD, MIN RADIUS						UNLESS OTHERWISE SPECIFIED	M M M M M M M M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
	BODY: CONTACTS: CABLE: Vo FLEX COUPLING: INSERT: O-RING:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI POLYAMIDE N/A	LE OD, MIN RADIUS						UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	M M M M M M M M M M M M M M M M M M M	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
	BODY: CONTACTS: CABLE: V( FLEX COUPLING: INSERT: O-RING: APPROVALS	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI POLYAMIDE N/A	LE OD, MIN RADIUS						UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	<ul> <li>DRAWN BY</li> <li>DRAWN DATE</li> <li>CHECKED BY</li> </ul>	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
	BODY: CONTACTS: CABLE: V( FLEX COUPLING: INSERT: O-RING: APPROVALS US:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI POLYAMIDE N/A UL LISTED	LE OD, MIN RADIUS			PROPRIETARY AND CONFIDENTIAL	VOLTS	42VDC	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	<ul> <li>DRAWN BY</li> <li>DRAWN DATE</li> <li>CHECK DATE</li> </ul>	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
	BODY: CONTACTS: CABLE: Vo FLEX COUPLING: INSERT: O-RING: APPROVALS US: CANADA:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI POLYAMIDE N/A UL LISTED C-UL LISTED	LE OD, MIN RADIUS			THE INFORMATION CONTAINED IN THIS	VOLTS	42VDC	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	<ul> <li>DRAWN BY</li> <li>DRAWN DATE</li> <li>CHECKED BY</li> </ul>	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
	BODY: CONTACTS: CABLE: V( FLEX COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS: CE:	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI POLYAMIDE N/A UL LISTED C-UL LISTED YES	LE OD, MIN RADIUS			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	AMPS	1.5A	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	<ul> <li>DRAWN BY</li> <li>DRAWN DATE</li> <li>CHECK DATE</li> </ul>	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB
	BODY: CONTACTS: CABLE: V( FLEX COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS: CE: RATINGS	GOLD PLATED CC STYLE: AWM CAT 5e AWG: 24 AWG JACKET: TEAL TPE OLTAGE: 600V SHIELD: BRAIDED CYCLES: 1MM @ 10X CABL NICKEL PLATED BI POLYAMIDE N/A UL LISTED C-UL LISTED YES	LE OD, MIN RADIUS RASS			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	<ul> <li>DRAWN BY</li> <li>DRAWN DATE</li> <li>CHECK DATE</li> </ul>	IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB IDE45WB

DE45WE	8-4MP-RJ45S-0.5	M 20" [0.5m]	NO					
DE45WE	8-4MP-RJ45S-1M	40" [1m]	YES					
DE45WE	8-4MP-RJ45S-1.5	M 59" [1.5m]	NO					
DE45WE	8-4MP-RJ45S-2M	79" [2m]	YES					
DE45WE	8-4MP-RJ45S-3M	118" [3m]	NO					
DE45WE	8-4MP-RJ45S-4M	157" [4m]	NO					
DE45WE	8-4MP-RJ45S-5M	197" [5m]	YES					
DE45WE	8-4MP-RJ45S-6M	236" [6m]	NO					
DE45WE	8-4MP-RJ45S-10N	M 393" [10m]	YES					
PARTS LISTED AS NOT BEING STANDARD MAY HAVE MINIMUM ORDER QUANTITIES								
JJH	MENCOM	CORPORATION						
08/24/2023	MERCOM							
JJH	TITLE:							
08/25/2023			A					
:	SIZE DWG. NO.		REV					
	B MDE45W	B-4MP-RJ45S-2	ZZ C					
	SCALE: 3:2 WEIGH	HT: SHE	ET 1 OF 1					
	2	1						

STD?

L

D

1