



CONNECTION MADE VIA SCREW TERMINALS

MATERIALS	
B BODY:	BLACK POLYAMIDE
CONTACTS:	GOLD COPPER ALLOY
COUPLING:	NICKEL PLATED COPPER ALLOY
INSERT:	POLYAMIDE
O-RING:	NBR
GLAND SEAL:	NBR
RATINGS:	
AMPS:	4A max
VOLTS:	250V max
CABLE RANGE:	18AWG - 24AWG
MIN WIRE SIZE:	0.157" - 0.315" (4mm - 8mm) OD
TEMP RATING:	-40°F - 185°F [-40°C - 85°C]
PROTECTION:	NEMA 1, 3, 4, 6P IEC IP67
APPROVALS:	
US:	UL LISTED
CANADA:	C-UL LISTED
RoHS:	YES
CE:	YES

Voltage rating is 250V or the rating of the cable, whichever is less.

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	DRAWN BY	JJH	MENCOM CORPORATION
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	01/03/2020	
CHECKED BY	ADM		
CHECK DATE	01/03/2020		
COMMENTS:			
SIZE	DWG. NO.		REV
B	MEC-5MP-FW09-R		A
SCALE: 2:1	WEIGHT:		SHEET 1 OF 1