	8	7		6	5	4		3			2	1	
PIN #	COLOR												
1	ORANGE												
	BLUE												
	WHITE w/				[
	RED w/BL				L	V							
5	GREEN w/	BLACK											
6	ORANGE	w/BLACK					65						
7	RED						2.5						
8	GREEN / Y	ELLOW											
9	BLACK					I M M AL			_				
	WHITE		e										
				•			(
								64	1 ·		7		
				[10.3]					5		<u> </u>		070
				Ğ.41						P/N		L	STD
										MIN-10FF	YX-3-R	36" [0.9M]	YES
										MIN-10FF	YX-6-R	72" [1.8M]	YES
									-	MIN-10FF	YX-12-R	144" [3.7M]	YES
									_	MIN-10FF	2X-15-R	180" [4.6M]	NO
										MIN-10FF		240" [6.1M]	YES
MATERIAL	S												
BODY:		BLACK PVC								MIN-10FF	PX-30-R	360" [9.1M]	YES
CONTACT	rs:	GOLD PLATED COPPER A								MIN-10FF	Y-40-R	480" [12.2M]	NO
CABLE:	STYLE:	A \A/AA											
		18 AWG								MIN-10FF	2X-50-R	600" [15.2M]	NO
		YELLOW PVC				1.125"-16 UN	/			MIN-10FF	Y-60-R	720" [18.3M]	NO
	VOLTAGE:					FEMALE							
	SHIELD:					THREAD -	/					1200" [30.5M]	
COUPLING		NICKEL PLATED BRASS										NOT BEING STAN	
INSERT:		YELLOW PVC									VE MINIM	UM ORDER QUA	ANIIIES
O-RING:		N/A						UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		ADM 01/31/2024	MENCO	OM CORPORA	TION
APPROVA	LS							AND [MM]	DRAWN DATE CHECKED BY		TLE:		
US:		UL LISTED								02/02/2024			
	:	C-UL LISTED											
CANADA:		YES			PROPRIETARY AND CONFIDENTIAL	VOLTS	300V						
CANADA: ROHS:		YES			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	AMPS	4A	MATERIAL	COMMENTS	: SIZ	E DWG. NO		REV
	A:	-					4/1						
ROHS: CE & UKC	A:				MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHO			FINISH	_		M	N-10FPX-77-R	
ROHS: CE & UKC RATINGS		UL TYPE 4 & 12, IEC IP69					105°C	FINISH	_			N-10FPX-ZZ-R	HEET 1 OF