												I	
		EMALE											
PIN#		PIN#											
F IIN #													
1		1											
2		2											
3		3											
Δ		4											
-		-											
5		5											
	ETC.												
12		12											
ģ			[78] 3.1		[78] 3.1								
No.					1 125-1	6 UN2B				TABLE A P/N MIN-12MF		L 36" [0.9m]	
MATERIAL						6 UN2B				P/N	P-3-C011		YE
	.s	BLACK PVC				6 UN2B E THRE	AD (2X)			P/N MIN-12MF MIN-12MF	P-3-C011	36" [0.9m] 72" [1.8m]	YE: YE:
BODY:		BLACK PVC GOLD PLATED COPPER A					AD (2X)			P/N MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011	36" [0.9m] 72" [1.8m] 144" [3.6m]	YE: YE: YE:
BODY: CONTACT							AD (2X)			P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m]	YE YE YE
BODY: CONTACT		GOLD PLATED COPPER A					AD (2X)			P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m]	YES YES YES YES
BODY: CONTACT	IS: STYLE: AWG:	GOLD PLATED COPPER A TC-ER 16 AWG					AD (2X)			P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m]	YES YES YES YES YES
BODY: CONTACT CABLE:	IS: STYLE: AWG: JACKET:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC					AD (2X)			P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m]	NO NO
MATERIAL BODY: CONTACT CABLE:	IS: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V					AD (2X)			P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011 P-60-C011	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m]	YES YES YES YES NO NO
BODY: CONTACT CABLE:	TS: STYLE: AWG: JACKET: VOLTAGE: SHIELD:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO					AD (2X)			P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m]	YES YES YES YES NO NO NO
BODY: CONTACT CABLE:	TS: STYLE: AWG: JACKET: VOLTAGE: SHIELD:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS					AD (2X)			P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011 LISTED AS NC	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND	YES YES YES YES NO NO NO NO
BODY: CONTACT CABLE: COUPLINC	TS: STYLE: AWG: JACKET: VOLTAGE: SHIELD:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS YELLOW PVC						TED: DRAWIN BY	GO	P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011 LISTED AS NC	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND M ORDER QUAN	YES YES YES YES NO NO NO NO
BODY: CONTACT CABLE: COUPLING INSERT: O-RING:	IS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: G:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS					UNLESS OTHERWISE SPECIF DIMENSIONS ARE IN INCHES		GO 02/06/2024	P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011 LISTED AS NC	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND	YES YES YES YES NO NO NO NO
BODY: CONTACT CABLE: COUPLINC INSERT: O-RING: APPROVA	IS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: G:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A					UNLESS OTHERWISE SPECIF	DRAWN DATE CHECKED BY	02/06/2024 JJH	P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011 LISTED AS NC	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND M ORDER QUAN	YES YES YES YES NO NO NO NO
BODY: CONTACT CABLE: COUPLING INSERT: O-RING: APPROVA US:	IS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: G:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED					UNLESS OTHERWISE SPECIF DIMENSIONS ARE IN INCHES	DRAWN DATE	02/06/2024	P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011 LISTED AS NC	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND M ORDER QUAN	YES YES YES YES NC NC NC NC NC
BODY: CONTACT CABLE: COUPLING INSERT: O-RING: APPROVA US: CANADA:	IS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: G:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED			FEMAL	E THRE	UNLESS OTHERWISE SPECIF DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY	02/06/2024 JJH	P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011 LISTED AS NC	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND M ORDER QUAN	YE: YE: YE: YE: NC NC NC NC
BODY: CONTACT CABLE: COUPLING INSERT: O-RING: APPROVA US: CANADA: ROHS:	IS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: G:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED YES					UNLESS OTHERWISE SPECIF DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY	02/06/2024 JJH 02/07/2024	P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011 LISTED AS NC VE MINIMU/	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND M ORDER QUAN	YE: YE: YE: YE: NC NC NC NC NC
BODY: CONTACT CABLE: COUPLINC INSERT: O-RING: APPROVA	IS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: G:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	FEMAL	E THRE	UNLESS OTHERWISE SPECIF DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY CHECK DATE	02/06/2024 JJH 02/07/2024	P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF TITLE: SIZE DWG. N	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-40-C011 P-40-C011 P-50-C011 P-60-C011 P-100-C011 LISTED AS NC VE MINIMU/	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND M ORDER QUAN	YES YES YES YES NC NC NC NC NC NC NC NC
BODY: CONTACT CABLE: COUPLING INSERT: O-RING: APPROVA US: CANADA: ROHS:	IS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: G:	GOLD PLATED COPPER A TC-ER 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED YES		THE INFORMATION CONTAINED IN THIS	FEMAL	E THRE	UNLESS OTHERWISE SPECIF DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY CHECK DATE	02/06/2024 JJH 02/07/2024	P/N MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF MIN-12MF TITLE: SIZE DWG. N	P-3-C011 P-6-C011 P-12-C011 P-20-C011 P-30-C011 P-30-C011 P-50-C011 P-50-C011 P-60-C011 ISTED AS NO VE MINIMU/ COM CC	36" [0.9m] 72" [1.8m] 144" [3.6m] 240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] DT BEING STAND M ORDER QUAN	YES YES YES YES NO NO NO NO

