



MATERIALS	
SHELL:	STAINLESS STEEL
CONTACTS:	GOLD PLATED COPPER ALLOY
INSERT:	YELLOW PVC
O-RING:	NBR
NUT:	ZINC PLATED STEEL
APPROVALS	
US:	UL LISTED
CANADA:	C-UL LISTED
ROHS:	YES
CE & UKCA:	YES
RATINGS	
PROTECTION CLASS:	UL TYPE 4 & 12, IEC IP69

AMPERAGE AND VOLTAGE ARE WIRE DEPENDANT. RATINGS LISTED ARE BASED ON 600V, 14AWG WIRE (WITH ONE WIRE BEING A GROUND). SMALLER WIRES AND LOWER VOLTAGE RATINGS WILL LOWER THESE VALUES.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	600V
AMPS	18V MAX
TEMP:	105°C

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	ADM
	DRAWN DATE	09/06/2023
	CHECKED BY	JJH
	CHECK DATE	09/06/2023
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE: 3 POL FEM RECP.		
SIZE B	DWG. NO. MIN-2FR-SC-SS	REV B
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1