PIN #	COLC	R	_							
1	GREE	N/YELLOW	_							
2	BLAC	К	-							
	WHITI		-							
'			_							
	I					1				
~				L –						
								7/8-16UN		
							\ F	EMALE T	HREAD	
					[64]		\backslash	\backslash		
					2.5					
								A CONTRACTOR		A
				、				\$117		
			V.	· · · · · · · · · · · · · · · · · · ·				\$ (@, 4		[26]
										1.0
				/						
			A	<				۹ ال 🞽		1.0
			4							
				<						
		[9.9]							A starting of the start of the	
		[9.9] Ø.39		<						
		[9.9] Ø.39								
MATERIALS		[9.9] Ø.39								
MATERIALS BODY:		Ø.39							A Contraction of the second se	
MATERIALS BODY: CONTACTS:		[9.9] Ø.39 BLACK PVC GOLD PLATED COPPER ALL								
BODY:		Ø.39 Black pvc	LOY							
BODY: CONTACTS:		Ø.39 Black pvc	LOY							
BODY: CONTACTS: CABLE:	STYLE: AWG:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG	LOY							
BODY: CONTACTS: CABLE: J	STYLE: AWG: JACKET:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC								
BODY: CONTACTS: CABLE: J VC	STYLE: AWG: JACKET: DLTAGE:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V	LOY							
BODY: CONTACTS: CABLE: J VC	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO								
BODY: CONTACTS: CABLE: J VC COUPLING:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS								
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS BLACK PVC								
BODY: CONTACTS: CABLE: J VC COUPLING:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS								SPECIFIED: DRAWN BY
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT: O-RING:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS BLACK PVC							UNLESS OTHERWISE DIMENSIONS ARE IN AND [MM]	SPECIFIED: DRAWN BY INCHES DRAWN DAT
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT: O-RING: APPROVALS	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS BLACK PVC N/A							DIMENSIONS ARE IN	SPECIFIED: DRAWN BY INCHES DRAWN DAT CHECKED BY
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT: O-RING: APPROVALS US:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS BLACK PVC N/A							DIMENSIONS ARE IN	SPECIFIED: DRAWN BY INCHES DRAWN DAT
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT: O-RING: APPROVALS US: CANADA:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS BLACK PVC N/A UL LISTED C-UL LISTED							DIMENSIONS ARE IN	SPECIFIED: DRAWN BY INCHES DRAWN DAT CHECKED BY
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS BLACK PVC N/A UL LISTED C-UL LISTED YES					VOLTS	€00V	DIMENSIONS ARE IN AND [MM]	SPECIFIED: DRAWN BY INCHES DRAWN DAT CHECKED BY
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT: O-RING: APPROVALS US: CANADA:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS BLACK PVC N/A UL LISTED C-UL LISTED			THE INFORMATION CC DRAWING IS THE SOLE	NTAINED IN THIS PROPERTY OF	VOLTS AMPS	600V 13A	DIMENSIONS ARE IN AND [MM] MATERIAL	SPECIFIED: DRAWN BY INCHES DRAWN DAT CHECKED BY CHECK DATE
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS:	STYLE: AWG: JACKET: DLTAGE: SHIELD:	Ø.39 BLACK PVC GOLD PLATED COPPER ALL STOOW 16 AWG BLACK PVC 600V NO NICKEL PLATED BRASS BLACK PVC N/A UL LISTED C-UL LISTED YES			THE INFORMATION CO	NTAINED IN THIS PROPERTY OF ION. ANY RT OR AS A WHOLE			DIMENSIONS ARE IN AND [MM]	SPECIFIED: DRAWN BY INCHES DRAWN DAT CHECKED BY CHECK DATE

								_
MIN	I-3M	IP-3-	B	36"	[0.9m]	YES	
MIN	I-3M	IP-6-	B	72"	[1.8m]	YES	
MIN	I-3M	IP-12	2-B	144"	[3.7n	n]	YES	
MIN	I-3M	IP-1	5-B	180"	[4.6n	n]	NO	
MIN	I-3M	IP-20)-B	240"	[6.1n	n]	YES	
MIN	I-3M	IP-30)-B	360"	[9.1n	n]	YES	В
MIN	I-3M	IP-4()-B	480"	[12.2r	n]	NO	
MIN	I-3M	IP-50)-B	600"	[15.2r	n]	NO	
MIN	I-3M	IP-60)-B	720"	[18.3r	n]	NO	
MIN	I-3M	IP-1()0-В	1200"	[30.5	m]	NO	
	-		-	NOT BE				
DM		MEN	ICO	мсс		RATIO	NC	
JJH)2/2023	TITLE	E:						A
	size B	DWG		N-3MF	P-77-B		REV	_
	SCAL	E: 1:1	WEIC			SHEET	[] OF]	_
	2		_			1		

С

STD?

L

1

P/N