		8	7	6	5	4		3			2	1	
	PIN#	COLOR			Y.			1					
	1	GREEN / YELLC	W										
D	2	BLACK											C
	3	WHITE											
С				L M20x1.5		—7/8-16l	JN2A			[25.4] 1.00	P/N		C
->											MIN-3MR-0.3M	/_M 20	12" [0.3M]
											MIN-3MR-0.5M		20" [0.5M]
В				[6.1]	[17.0]						MIN-3MR-0.6M		24" [0.6M]
	MATERIALS	S		.24	.67	-					MIN-3MR-1M-		40" [1M]
	SHELL:	ANODIZED	ALUMINUM	۲_۲	.07						MIN-3MR-2M-		79" [2M]
	CONTACTS WIRES:	S: GOLD PLAT	ED COPPER ALLOY								MIN-3MR-3M-		118" [3m]
	WIKES.	STYLE: UL1015									MIN-3MR-4M-		157" [4M]
		AWG: 16 AWG									MIN-3MR-5M-		197" [4M]
	۱	JACKET: PVC VOLTAGE: 600V											
	INSERT:	YELLOW PV	C								MIN-3MR-10M Other Lenc		393" [10M] Vailable
	O-RING:	NBR									PLEASE C	ONSULT FA	CTORY
	NUT:	NICKEL PLA	IED RKY22					UNLESS OTHERWISE SPECIFIED	DRAWN BY	ADM 09/21/2023	MENCOM C	CORPOR	ATION
	APPROVAL	LS						AND [MM]	CHECKED BY	JJH	TITLE:		
Α		UL LISTED							CHECK DATE	10/31/2023	3 PL MI	MIN REC	P A
	CANADA:					\/ <u>0</u> + 7							
	ROHS: CE & UKCA	YES A: YES			PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS	600V	MATERIAL	COMMENTS	:			
					DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	AMPS	13A				SIZE DWG. NO. MIN-3M		REV
	RATINGS				REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS	TEMP:	105°C	FINISH	_			R-ZZ-M20	
	PROTECTIC	ON CLASS: UL TYPE 4 8	12, IEC IP69		PROHIBITED.			DO NOT SCALE DRAWING			SCALE: 2:1 WEIGHT:		SHEET 1 OF 1