			5		3		2		1	
							REVISIONS			
					REV.	DESCRIPTION		DATE	APPROVED	
					A	REDRAWN IN SW		6/15/2006		
			[28]							
			Ø1.1							
		∕—7/8-16 UN2B					_			
		N								
		N								
		N								
		//								
		/								
			-	[92]						
				[92] 3.6 r	nom.					
					nom.		►			
					10m.		►			
					nom.					
					nom.					
/ATERIALS:]			nom.					
	BLACK POLYAMIDE				nom.					
BODY:	BLACK POLYAMIDE STAINLESS STEEL				nom.		_ _			
BODY: COUPLING: NSERT:	STAINLESS STEEL YELLOW PVC				nom.		_ _			
BODY: COUPLING: NSERT: CONTACTS:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY				10m.					
BODY: COUPLING: NSERT: CONTACTS:	STAINLESS STEEL YELLOW PVC									
BODY: COUPLING: NSERT: CONTACTS:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY				UNLESS OTHERWISE SPECIFIED			DM CORPO	RATION	
BODY: COUPLING: NSERT: CONTACTS: GLAND SEAL:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY NBR					DRAWN BEM	MENCC	OM CORPO	RATION	
BODY: COUPLING: NSERT: CONTACTS: GLAND SEAL: SPECIFICATIONS:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY NBR				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DM CORPO	RATION	
BODY: COUPLING: NSERT: CONTACTS: GLAND SEAL: SPECIFICATIONS: /OLTS:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY NBR 600V				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BEM CHECKED	MENCC	DM CORPO	RATION	
BODY: COUPLING: NSERT: CONTACTS: GLAND SEAL: SPECIFICATIONS: /OLTS: AMPS:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY NBR 600V 10A				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BEM CHECKED ENG APPR. MFG APPR. Q.A.	MENCC	DM CORPO	RATION	
BODY: COUPLING: NSERT: CONTACTS: GLAND SEAL: SPECIFICATIONS: /OLTS: AMPS: SEAL:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY NBR 600V 10A IP67		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BEM CHECKED ENG APPR. MFG APPR.	TITLE:			
BODY: COUPLING: NSERT: CONTACTS: GLAND SEAL: SPECIFICATIONS: /OLTS: AMPS: SEAL: IEMP:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY NBR 600V 10A IP67 -20°C - +100°C		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION, ANY		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	DRAWN BEM CHECKED ENG APPR. MFG APPR. Q.A.	TITLE:		REV	
MATERIALS: BODY: COUPLING: INSERT: CONTACTS: GLAND SEAL: SPECIFICATIONS: VOLTS: AMPS: SEAL: TEMP: WIRE RANGE: CABLE DIA.:	STAINLESS STEEL YELLOW PVC GOLD PLATED COPPER ALLOY NBR 600V 10A IP67		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BEM CHECKED ENG APPR. MFG APPR. Q.A.	TITLE:		REV	

