



MATERIALS BLACK POLYAMIDE BODY: GOLD PLATED COPPER ALLOY CONTACTS: CABLE SEAL: NBR **INSERT: YELLOW PVC NICKEL PLATED BRASS COUPLING: RATINGS** AMPS: 14AWG - 15A max 16AWG - 10A max 18AWG - 8A max 20-22AWG - 4A max **VOLTS: 600V MAX** SEAL: **IP67** CABLE RANGE: 14AWG - 22AWG 0.20" - 0.51" (5mm - 13mm) OD **APPROVALS** US: **UL LISTED** CANADA: **C-UL LISTED**

Voltage rating is 600V or the rating of the cable, whichever is less.

Connections made via screw terminal

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

	UNLESS OTHERWISE SPECIFIED:		NAME	11 L	ICOM CORPOR	Λ TIC	116
	DIMENSIONS ARE IN INCHES AND [MM]	DRAWN	BEM	/VILI	ACOM CONTON		Л٧
		CHECKED		TITLE:			
		ENG APPR.					
		MFG APPR.					
		Q.A.					
		COMMENTS:					
	MATERIAL			SIZE DWG. NO.			RE\
	FINISH			В	MIN-4FP-FW		В
	DO NOT SCALE DRAWING			SCALE: 2:1	WEIGHT:	SHEET	1 OF

	DLIVI						
		TITLE	:				
							Α
		CLZE				DEV	
			DWG			REV	
		В		MIN-4FP-FW		В	
	SCALE: 2:1		E: 2:1	WEIGHT:	SHEE	T 1 OF 1	