	8			6	5			3	
PIN #	COLOR				¥				
1	BLACK								
2	WHITE								
3	RED								
4	GREEN	/ YELLOW							
				-	L				
_									
							44		
							1.8		
				i and a second s					
								[38]	
				Г	~			1.5	
					7				
				[10.					
				ϕ .	2				
				[10. Ø.4	/ 2				
				ϕ .4	/ 2				
Þ				[10. Ø.4	/ 2				
				[10. Ø.4	/ 2				
				[10. Ø.4	/ 12				
MATERIAIS				[10. Ø.4	/ !2				
MATERIALS				[10. Ø.4	/ 12				
BODY:	YEL	LOW PVC	ER ALLOY	[10. Ø.4	/ !2	、 (111 - 11			
	YEL	LOW PVC DLD PLATED COPP	ER ALLOY		/ 12				
BODY: CONTACTS	YEL	DLD PLATED COPP	ER ALLOY	(10. Ø.2	/ 12			[25]	
BODY: CONTACTS	YEL S: GO	DLD PLATED COPP	ER ALLOY	(10. Ø.2				25 1.0	
BODY: CONTACTS CABLE:	S: GO STYLE: STC AWG: 16 JACKET: YEL	DLD PLATED COPP DOW AWG LOW PVC	ER ALLOY	[10. Ø.2					
BODY: CONTACTS CABLE:	STYLE: STC AWG: 16 JACKET: YEL OLTAGE: 600	DLD PLATED COPP DOW AWG LOW PVC DV	ER ALLOY		12				
BODY: CONTACTS CABLE: V	STYLE: STC AWG: 16 JACKET: YEL OLTAGE: 600 SHIELD: NO	DLD PLATED COPP DOW AWG LOW PVC DV			12				
BODY: CONTACTS CABLE: V	STYLE: STC AWG: 16 JACKET: YEL OLTAGE: 600 SHIELD: NO	DID PLATED COPP DOW AWG LOW PVC DV CKEL PLATED BRAS			12 7/8- FEN	1ALE			
BODY: CONTACTS CABLE: V COUPLING INSERT:	STYLE: STC AWG: 16 JACKET: YEL OLTAGE: 600 SHIELD: NO SHIELD: NIC	DID PLATED COPP DOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC			12 7/8- FEN			1.0	
BODY: CONTACTS CABLE: V	STYLE: STC AWG: 16 JACKET: YEL OLTAGE: 600 SHIELD: NO	DID PLATED COPP DOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC			12 7/8- FEN	1ALE			Dioterror
BODY: CONTACTS CABLE: V COUPLING INSERT: O-RING:	YEL S: GO STYLE: STC AWG: 16 / JACKET: YEL /OLTAGE: 600 SHIELD: NO :: NIC YEL N//	DID PLATED COPP DOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC			12 7/8- FEN	1ALE		1.0	D: DRAWN BY DRAWN DATE CHECKED BY
BODY: CONTACTS CABLE: V COUPLING INSERT: O-RING: APPROVAL	STYLE: STC AWG: 16 / JACKET: YEL /OLTAGE: 600 SHIELD: NO : NIC SHIELD: N//	DID PLATED COPP DOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC			12 7/8- FEN	1ALE		UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	DRAWN DATE
BODY: CONTACTS CABLE: V COUPLING INSERT: O-RING:	STYLE: STC AWG: 16 JACKET: YEL OLTAGE: 600 SHIELD: NO SHIELD: NO YEL N/J	DID PLATED COPP DOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC			12 7/8- FEN	1ALE		UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY
BODY: CONTACTS CABLE: V COUPLING INSERT: O-RING: APPROVAL US:	STYLE: STC AWG: 16 JACKET: YEL OLTAGE: 600 SHIELD: NO SHIELD: NO YEL N/J	DID PLATED COPP OOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC A LISTED JL LISTED			12 7/8- FEN THR	IALE EAD —		UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY CHECK DATE
BODY: CONTACTS CABLE: V COUPLING INSERT: O-RING: APPROVAL US: CANADA:	STYLE: GC STYLE: STC AWG: 16 / JACKET: YEL /OLTAGE: 600 SHIELD: NO SHIELD: NO SHIELD: NIC SHIELD: NIC SHIELD: NIC C-U YEL V/J	DID PLATED COPP OOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC A LISTED JL LISTED			12 778- FEM FEM THR	VOLTS	600V	UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY CHECK DATE
BODY: CONTACTS CABLE: V COUPLING INSERT: O-RING: APPROVAL US: CANADA: ROHS: CE & UKCA	STYLE: GC STYLE: STC AWG: 16 / JACKET: YEL /OLTAGE: 600 SHIELD: NO SHIELD: NO SHIELD: NIC SHIELD: NIC SHIELD: NIC C-U YEL V/J	DID PLATED COPP OOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC A LISTED JL LISTED			POPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	VOLTS AMPS	10A	UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY CHECK DATE
BODY: CONTACTS CABLE: V COUPLING INSERT: O-RING: APPROVAL US: CANADA: ROHS: CE & UKCA RATINGS	YEL S: GO STYLE: STC AWG: 16 / JACKET: YEL OLTAGE: 600 SHIELD: NO SHIELD: NO SHIELD: NO SHIELD: NO SHIELD: NO SHIELD: NO SHIELD: YEL N//	DID PLATED COPP OOW AWG LOW PVC DV CKEL PLATED BRAS LOW PVC A LISTED JL LISTED	S		POPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	VOLTS AMPS		UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY

		P/N				L	S	STD?	
		MIN	I-4FP-3-R	2	36"	[0.9m		YES	
		MIN	I-4FP-6-R	2	72"	[1.8m]	YES	
		MIN	I-4FP-12-	R	144"	[3.7m	ן [ו	YES	В
		MIN	I-4FP-20-	R	240"	[6.1m	י [ו	YES	
		MIN	I-4FP-30-	R	360"	[9.1m	ן [ו	YES	
		MIN	I-4FP-40-	R 4	480"	[12.2r	n]	NO	
		MIN	I-4FP-50-	R	600"	[15.2r	n]	YES	
		MIN	I-4FP-60-	R	720"	[18.3r	n]	NO	
		MIN	I-4FP-100)-R 1	200"	[30.5	m]	NO	
		F	ARTS LISTEI MAY REC						
specified:	DRAWN BY	ADM	MENO	$\sim \sim \sim$					
NCHES	DRAWN DATE	10/20/2023							
	CHECKED BY	JJH	TITLE:						
	CHECK DATE	10/31/2023							A
	COMMENTS:		SIZE DWG. NO.						
			B		I-4FP-	77 D		REV	
AWING			SCALE: 1:1	WEIGH	T:		SHEET	1 OF 1	
			2		1	1			

С

D