	8	7	6		5	4	3		2	1
PIN#	COLO	R								
1	BLAC	ĸ								
- I - 2										
2	WHITE									
3	RED									
4	GREE	N/YELLOW								
_			L —							
			M20x1.	5	/7/	/8-16 UN2A				
				N M						
			Ň		A HANANA					
					-1 INDIANANAN	/ _ ◎	<mark>⁴ '@) \</mark> ∭\\ []	25.4		
					-V IINDANN		³ ² //////	1.0		
					Y LAYAYAYA					
			\`							
			``							
۵			Ň					V.	P/N	L
			X						P/N	L
			` [6.	.1]	[17]					
				.1]	[17] .67				MIN-4FR-1-18-M20	12" [0.3m
MATERIALS			.2		[17] .67				MIN-4FR-1-18-M20 MIN-4FR-2-18-M20	12" [0.3m 24" [0.6m
SHELL:			.2		[17] .67				MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20	12" [0.3m 24" [0.6m 36" [0.9m
SHELL: CONTACTS		CLEAR ANODIZED ALUMINUM GOLD PLATED COPPER ALLOY	.2		[17] .67				MIN-4FR-1-18-M20 MIN-4FR-2-18-M20	12" [0.3m 24" [0.6m
SHELL:	S:		.2		[17] .67				MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20	12" [0.3m 24" [0.6m 36" [0.9m
SHELL: CONTACTS	S: STYLE:	GOLD PLATED COPPER ALLOY	.2		[17] .67				MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m]
SHELL: CONTACTS WIRES:	S: STYLE: AWG: JACKET:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC	.2		[17] .67				MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m]
SHELL: CONTACTS WIRES:	S: STYLE: AWG:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V	.2		[17] .67				MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-10-18-M20	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m]
SHELL: CONTACTS WIRES: VINSERT:	S: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC	.2						MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-10-18-M20 OTHER LENGTHS AR	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE
SHELL: CONTACTS WIRES: VIRES: V INSERT: O-RING:	S: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC NBR	.2						MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-10-18-M20	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE
SHELL: CONTACTS WIRES: VINSERT:	S: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC	.2					RAWN BY ADM RAWN DATE 11/07/202	MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-10-18-M20 OTHER LENGTHS AR PLEASE CONSULT	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE FACTORY
SHELL: CONTACTS WIRES: VIRES: V INSERT: O-RING:	S: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC NBR	.2				DIMENSIONS ARE IN INCHES		MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-10-18-M20 OTHER LENGTHS AR PLEASE CONSULT	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE FACTORY
SHELL: CONTACTS WIRES: VIRES: V INSERT: O-RING: NUT: APPROVAL	S: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC NBR	.2				DIMENSIONS ARE IN INCHES AND [MM]	RAWN DATE 11/07/202	MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-6-18-M20 OTHER LENGTHS AR PLEASE CONSULT MENCOM CORF	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE FACTORY PORATION
SHELL: CONTACTS WIRES: VINSERT: O-RING: NUT: APPROVAL	S: STYLE: AWG: JACKET: VOLTAGE: LS	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC NBR NICKEL PLATED BRASS	.2				DIMENSIONS ARE IN INCHES AND [MM]	RAWN DATE 11/07/2023 HECKED BY JJH	MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-10-18-M20 OTHER LENGTHS AR PLEASE CONSULT MENCOM CORF	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE FACTORY PORATION
SHELL: CONTACTS WIRES: VINSERT: O-RING: NUT: APPROVAL US:	S: STYLE: AWG: JACKET: VOLTAGE: LS	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC NBR NICKEL PLATED BRASS	.2		.6/	νοις στιον	DIMENSIONS ARE IN INCHES AND [MM]	RAWN DATE 11/07/2023 HECKED BY JJH HECK DATE 11/08/2023	MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-6-18-M20 OTHER LENGTHS AR PLEASE CONSULT MENCOM CORF	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE FACTORY PORATION
SHELL: CONTACTS WIRES: VIRES: V INSERT: O-RING: NUT: APPROVAL US: CANADA:	S: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC NBR NICKEL PLATED BRASS UL LISTED C-UL LISTED	.2	24	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS 300V	DIMENSIONS ARE IN INCHES AND [MM]	RAWN DATE 11/07/2023 HECKED BY JJH	MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-6-18-M20 OTHER LENGTHS AR PLEASE CONSULT MENCOM CORF	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE FACTORY PORATION
SHELL: CONTACTS WIRES: VIRES: V INSERT: O-RING: NUT: APPROVAL US: CANADA: ROHS: CE & UKCA	S: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC NBR NICKEL PLATED BRASS UL LISTED C-UL LISTED YES	.2	24	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	AMPS 8A	DIMENSIONS ARE IN INCHES DI AND [MM] C	RAWN DATE 11/07/2023 HECKED BY JJH HECK DATE 11/08/2023	MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-6-18-M20 MIN-4FR-10-18-M20 OTHER LENGTHS AR PLEASE CONSULT MENCOM CORF TITLE: 3 4 PL MIN FM	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE FACTORY PORATION RECP
SHELL: CONTACTS WIRES: VIRES: INSERT: O-RING: NUT: APPROVAL US: CANADA: ROHS: CE & UKCA RATINGS	S: STYLE: AWG: JACKET: VOLTAGE: LS	GOLD PLATED COPPER ALLOY UL 1007/1569 18 AWG PVC 300V YELLOW PVC NBR NICKEL PLATED BRASS UL LISTED C-UL LISTED YES	.2	24	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		DIMENSIONS ARE IN INCHES DI AND [MM] C	RAWN DATE 11/07/2023 HECKED BY JJH HECK DATE 11/08/2023	MIN-4FR-1-18-M20 MIN-4FR-2-18-M20 MIN-4FR-3-18-M20 MIN-4FR-4-18-M20 MIN-4FR-5-18-M20 MIN-4FR-6-18-M20 MIN-4FR-6-18-M20 OTHER LENGTHS AR PLEASE CONSULT MENCOM CORF	12" [0.3m 24" [0.6m 36" [0.9m 48" [1.2m 60" [1.5m] 72" 1.8m] 120" [3m] E AVAILABLE FACTORY PORATION RECP