8	7		6	5	4		3		2	1
PIN # COL	OR				, ,					
1 BLA	СК									
2 WHIT										
3 RED										
4 GRE	EN / YELLOW									
		L								
				/7/8-16 UN2A	N					
					-					
		1/2-14 NPT				_				
				man			A			
		Î								
							7		TABI	LEA
					 	<u>፼ \ </u> Y	[25.4]		P/N	
_						<u>⊜/////∕</u>				
-						"/// /	,		MIN-4FR-1-SS	12" [0.3m]
		V			AC					
							Y		MIN-4FR-2-SS	24" [0.6m]
									MIN-4FR-3-SS	36" [0.9m]
									MIN-4FR-4-SS	48" [1.2m]
MATERIALS		[10.5]		14] 55					MIN-4FR-5-SS	60" [1.5m]
SHELL: CONTACTS:	STAINLESS STEEL GOLD PLATED COPPER ALLOY	12		55					MIN-4FR-6-SS	72" [1.8m]
WIRES:									MIN-4FR-10-SS	120" [3.0m
	UL 1015 16 AWG								MIN-4FR-15-SS	- 180" [4.6m
JACKET									MIN-4FR-20-SS	
VOLTAGE										240" [6.1m
INSERT:	YELLOW PVC								PLEASE CON	S ARE AVAILABLE SULT FACTORY
O-RING: NUT:	NBR ZINC PLATED STEEL						UNLESS OTHERWISE SPECIFIED	D: DRAWN BY ADM		
							DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 10/23/2023		ORATION
APPROVALS US:	UL LISTED							CHECKED BY JJH CHECK DATE 10/31/2023	TITLE:	
US: CANADA:	C-UL LISTED								4 PL FEM RCF	P, 16AWG SS
	YES			PROPRIETARY AND CONFIDENTIAL	VOLTS	600V	_			
ROHS:	YES			PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	AMPS	10A	MATERIAL	COMMENTS:	SIZE DWG. NO.	REV
ROHS: CE & UKCA:	I LJ				7 U V U U	IUA				
CE & UKCA:				MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOL	E ΤΕλΛΡ·		FINISH		B MIN-4FR	-77-SS R
CE & UKCA: RATINGS	: UL TYPE 4 & 12, IEC IP69				TEMP:	105°C	FINISH DO NOT SCALE DRAWING		B MIN-4FR SCALE: 2:1 WEIGHT:	-ZZ-SS B