



[28] 1.1 [95] 3.7

MATERIALS			
BODY:	BLACK POLYAMIDE		
CONTACTS:	<b>GOLD PLATED COPPER ALLOY</b>		
CABLE SEAL:	NBR		
INSERT:	YELLOW PVC		
COUPLING:	NICKEL PLATED BRAS		
RATINGS			
41400	44000 450		
AMPS:	14AWG - 15A max		
	16AWG - 10A max		
	18AWG - 8A max		
	20-22AWG - 4A max		
VOLTS:	600V MAX		
SEAL:	IP67		
<b>CABLE RANGE:</b>	14AWG - 22AWG		
	0.31" - 0.67" (8mm - 17mm) OD		
APPROVALS			
	UL LISTED		
US: CANADA:	C-UL LISTED		

Voltage rating is 600V or the rating of the cable, whichever is less.

Connections made via screw terminal

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION. IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

	UNLESS OTHERWISE SPECIFIED:		NAME	٨.٨
-	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/64 ANGULAR: MACH±5° BEND ±5° TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.004	DRAWN	JJH	1
		CHECKED		TITLE:
		ENG APPR.		
		MFG APPR.		
		Q.A.		
		COMMENTS:		
	MATERIAL			SIZE D
	HZIMISH			<b>—</b>

DO NOT SCALE DRAWING

SIZE DWG. NO.

MIN-4MP-FWX

SCALE: 1:1 WEIGHT: SHEET 1 OF 1

MENCOM CORPORATION

7 6 5 4 3