		,		5		3			
PIN #	COLOR								
1	BLACK	-							
2	WHITE								
3	RED								
4	<b>GREEN / YELLOW</b>								
		L⁄	/						
			_	_	<u> </u>				
			64			HKEAU			
			2.	5					
							P/N	L	STD
						[25] 1.0			
	•						MIN-4MP-3-SS	36" [0.9m]	YES
							MIN-4MP-6-SS	72" [1.8m]	YES
	[10.7] _						MIN-4MP-12-SS	144" [3.7m]	YES
	Ø.42						MIN 4MD 45 00	400" [4 Cm]	
							MIN-4MP-15-SS	180 [4.6m]	NO
ATERIALS	~ · · -							180" [4.6m] 240" [6.1m]	
	YELLOW PVC						MIN-4MP-20-SS	240" [6.1m]	YES
ODY: CONTACTS:	YELLOW PVC	ER ALLOY					MIN-4MP-20-SS MIN-4MP-30-SS	240" [6.1m] 360" [9.1m]	YES YES
SODY: CONTACTS:	YELLOW PVC GOLD PLATED COPP	ER ALLOY					MIN-4MP-20-SS	240" [6.1m]	YES YES
BODY: CONTACTS:	YELLOW PVC GOLD PLATED COPP STYLE: STOOW	ER ALLOY					MIN-4MP-20-SS MIN-4MP-30-SS	240" [6.1m] 360" [9.1m]	YES YES NO
ODY: CONTACTS: CABLE:	YELLOW PVC GOLD PLATED COPP	ER ALLOY					MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m]	YES YES NO YES
BODY: CONTACTS: CABLE: J	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG	ER ALLOY					MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-60-SS	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m]	YES YES NO YES NO
BODY: CONTACTS: CABLE: J VC	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO						MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-100-SS	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m]	YES NO YES NO NO
BODY: CONTACTS: CABLE: J VC COUPLING:	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO STAINLESS STEEL	ER ALLOY					MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-100-SS PARTS LISTED AS	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] BEING NOT STAN	YES NO YES NO NO
ODY: CONTACTS: CABLE: J VC COUPLING: NSERT:	YELLOW PVC   GOLD PLATED COPP   STYLE:   STOOW   AWG:   16 AWG   JACKET:   YELLOW PVC   DLTAGE:   600V   SHIELD:   NO   STAINLESS STEEL   YELLOW PVC						MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-100-SS PARTS LISTED AS MAY REQUIR	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m]	YES YES NO YES NO NO
BODY: CONTACTS: CABLE: J VC COUPLING: NSERT: D-RING:	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO STAINLESS STEEL YELLOW PVC N/A					AND [MM]	MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-60-SS MIN-4MP-100-SS PARTS LISTED AS MAY REQUIR	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] BEING NOT STAN	YES NO YES NO NO NO NDAR ERS
BODY: CONTACTS: CABLE: J VC COUPLING: NSERT: D-RING: APPROVALS	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO STAINLESS STEEL YELLOW PVC N/A					DIMENSIONS ARE IN INCHES AND [MM]	MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-60-SS MIN-4MP-100-SS PARTS LISTED AS MAY REQUIR	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] BEING NOT STAN MINIMUM ORD	YES NO YES NO NO NDAR ERS
SODY: CONTACTS: CABLE: J VC COUPLING: NSERT: D-RING: NPPROVALS IS:	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO STAINLESS STEEL YELLOW PVC N/A UL LISTED					DIMENSIONS ARE IN INCHES AND [MM]	MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-60-SS MIN-4MP-100-SS PARTS LISTED AS MAY REQUIR	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] BEING NOT STAN E MINIMUM ORD	YES NO YES NO NO NO NDAR ERS
BODY: CONTACTS: CABLE: J VC COUPLING: NSERT: D-RING: APPROVALS JS: CANADA:	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO STAINLESS STEEL YELLOW PVC N/A UL LISTED C-UL LISTED					DIMENSIONS ARE IN INCHES AND [MM]	MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-60-SS MIN-4MP-100-SS PARTS LISTED AS MAY REQUIR	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] BEING NOT STAN MINIMUM ORD	YES NO YES NO NO NO NDAR ERS
BODY: CONTACTS: CABLE: J VC COUPLING: NSERT: O-RING: APPROVALS JS: CANADA: ROHS:	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO STAINLESS STEEL YELLOW PVC N/A UL LISTED			PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS 600V	DIMENSIONS ARE IN INCHES C AND [MM]	MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-60-SS MIN-4MP-100-SS PARTS LISTED AS MAY REQUIR DRAWN BY APR MENCOM DRAWN DATE 11/10/2023 THECKED BY JJH TITLE: COMMENTS:	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] BEING NOT STAN MINIMUM ORD	YES NO YES NO NDAR ERS
BODY: CONTACTS: CABLE: J VC COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS:	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO STAINLESS STEEL YELLOW PVC N/A UL LISTED C-UL LISTED YES			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	AMPS 10A	DIMENSIONS ARE IN INCHES AND [MM]	MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-60-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-60-SS MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MIN-4MP-60-SS MIN-4MP-60-SS MAY REQUIR MAY REQUIR MAY REQUIR MIN-4MP-60-SS MIN-4MP-60-SS MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MIN-4MP-60-SS MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MIN-4MP-60-SS MAY REQUIR MAY REQUIR	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] BEING NOT STAN E MINIMUM ORD CORPORATIO	YES NO YES NO NO NO NO RERS
VC COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS: CE: RATINGS	YELLOW PVC GOLD PLATED COPP STYLE: STOOW AWG: 16 AWG JACKET: YELLOW PVC DLTAGE: 600V SHIELD: NO STAINLESS STEEL YELLOW PVC N/A UL LISTED C-UL LISTED YES			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		DIMENSIONS ARE IN INCHES C AND [MM]	MIN-4MP-20-SS MIN-4MP-30-SS MIN-4MP-40-SS MIN-4MP-50-SS MIN-4MP-50-SS MIN-4MP-60-SS MIN-4MP-60-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-100-SS MIN-4MP-60-SS MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MIN-4MP-60-SS MIN-4MP-60-SS MAY REQUIR MAY REQUIR MAY REQUIR MIN-4MP-60-SS MIN-4MP-60-SS MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MIN-4MP-60-SS MAY REQUIR MAY REQUIR MAY REQUIR MAY REQUIR MIN-4MP-60-SS MAY REQUIR MAY REQUIR	240" [6.1m] 360" [9.1m] 480" [12.2m] 600" [15.2m] 720" [18.3m] 1200" [30.5m] BEING NOT STAN EMINIMUM ORD CORPORATION CORPORATION PLUG 16AW	NO NO NDAR ERS