17	8		7	6	5	4		3		2	1	
PIN #	COLO	DR										
1	BLAC	ж										
2	WHIT	E										
3	RED											
4		EN / YELLOW										
	UNE											
			1				8-16 UN					
			L	۲.	64]		FEMALE THREAD					
					2.5							
		ļ							P	N	L	STD
								[26]	Μ	IN-4MP-3	36" [0.9m]	YE
	_							? I.U		IN-4MP-6	72" [1.8m]	YE
		[10.7]				San	S S S S S S S S S S S S S S S S S S S			IN-4MP-8	96" [2.4m]	NO
		Ø.42								IN-4MP-12	144" [3.7m]	YES
										IN-4MP-15	180" [4.6m]	NO
MATERIAL	S									IN-4MP-20	240" [6.1m]	YE
BODY:		BLACK PVC										
CONTACT	TS:	GOLD PLATED COPPE	R ALLOY						N	IN-4MP-30	360" [9.1m]	YES
CABLE:									Μ	IN-4MP-40	480" [12.2m]	NO
		STOOW							м	IN-4MP-50	600" [15.2m]	YES
		16 AWG YELLOW PVC										
,	VOLTAGE:								IVI	IN-4MP-60	720" [18.3m]	NO
	SHIELD:								M	IN-4MP-100	1200" [30.5m]	NO
COUPLING		NICKEL PLATED BRASS	3							PARTS LISTED	AS BEING NOT STANI	DARD
INSERT:		YELLOW PVC								MAY REQU	JIRE MINIMUM ORDE	RS
O-RING:		N/A						UNLESS OTHERWISE SPECIFIED	D: DRAWN BY A		COM CORPORA	
								DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 11/09	72023		
APPROVA	ALS								CHECKED BY J CHECK DATE 11/09			
US:	•	UL LISTED C-UL LISTED								4 PL	MAL PLUG 16A	WG
CANADA: ROHS:	•	YES					(00) (
CE & UKC	Δ:	YES			PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS	600V	MATERIAL	COMMENTS:		10	55
	·/~\•	. LJ			DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	AMPS	10A			SIZE DWG. N		RE
RATINGS					REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF	TEMP:	105°C	FINISH		B	MIN-4MP-ZZ	
		UL TYPE 4 & 12, IEC IP	40		MENCOM CORPORATION IS PROHIBITED.			DO NOT SCALE DRAWING		SCALE: 1:1	WEIGHT: SF	HEET 1 OF