8	7	6	5	2	Ļ	3		2		1
PIN # COLOR										
1 BLACK										
2 WHITE										
3 RED										
4 GREEN / Y	(FLLOW									
	L —				 	18.2] .72				
			7/8-16 UN	2A		./2				
				[3.2]			[18.2] .72	[30] 1.18 Sq		
		[3.5]	_	©.2∫ Ø.13				P/N		
			02 0]	4x					I-4MR-1-PM	∟ 12" [0.3n
			23.9]							
MATERIALS		٦	.74						I-4MR-2-PM	24" 0.6m
SHELL:	CLEAR ANODIZED ALUMINUM	-						MIN	I-4MR-3-PM	36" [0.9n
CONTACTS:	GOLD PLATED COPPER ALLOY							MIN	-4MR-4-PM	48" [1.2n
WIRES:		_								
	LE: UL 1007/1569								I-4MR-5-PM	60" [1.5n
	G: 22 AWG	_						MIN	I-4MR-6-PM	72" [1.8n
	ET: PVC	_						ВЛІВ		
	SE: 300V	_							I-4MR-10-PM	120" [3m
NSERT:	YELLOW PVC	_						0	THER LENGTHS AF PLEASE CONSUL	
GASKET: NUT:	NBR N/A	-				UNLESS OTHERWISE SPECIFIED	DRAWN BY ADM			
		_				DIMENSIONS ARE IN INCHES	DRAWN DATE 11/13/2023	ME	NCOM CORF	ORATION
APPROVALS		-				AND [MM]	CHECKED BY JJH	TITLE:		
JS:	UL LISTED	-					CHECK DATE 11/14/2023			
CANADA:	C-UL LISTED	_								
ROHS:	YES		PROPRIETARY AND CONFIDENTIAL	VOLTS	300V			_		
CE & UKCA:	YES		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	AMPS		MATERIAL	COMMENTS:	SIZE DW	G. NO.	REV
			MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE		4A	FINISH		B	MIN-4MR-ZZ	
RATINGS			WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS	TEMP:	105°C				1V111 N-41V11X-LL	
	SS: UL TYPE 4 & 12, IEC IP69		MENCOM CORPORATION IS					SCALE: 2:1	WEIGHT:	SHEET 1 OF

