	8							
	PIN# COL	OR						
	1 RED	w/WHITE						
	2 RED							
	3 GRE	EN/YELLOW						
	4 RED	w/YELLOW						
	5 RED	w/BLACK						
_								
			I					
			L			7/8-16 UI		
				64		FEMALE 1	THREAD	
2				2.5				
•				2.0	/	and the second s		
					<i>sti</i>			
					<i>M</i>		[26]	
			$\langle \langle \rangle$		31(((
	-		\prec				1.0	
					·	A DO DO DO DO DO	· · · · ·	
		φ .51						
3	MATERIALS]					
	BODY:	YELLOW PVC	-					
-	BODY: CONTACTS:	YELLOW PVC GOLD PLATED COPPER ALLOY	-					
	CONTACTS: CABLE:	GOLD PLATED COPPER ALLOY	-					
	CONTACTS: CABLE: STYLE:	GOLD PLATED COPPER ALLOY STOOW						
	CONTACTS: CABLE: STYLE: AWG:	GOLD PLATED COPPER ALLOY STOOW 16 AWG	-					
	CONTACTS: CABLE: STYLE: AWG: JACKET:	GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC						
	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V						
-	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD:	GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO						
-	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD: COUPLING:	GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS						
	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD:	GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO					UNLESS OTHERWISE SPECIFIED:	DRAWN BY
	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD: COUPLING: INSERT: O-RING:	GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC					UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE
	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD: COUPLING: INSERT: O-RING: APPROVALS	GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A					DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY
	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD: COUPLING: INSERT: O-RING: APPROVALS US:	GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A					DIMENSIONS ARE IN INCHES	DRAWN DATE
	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD: COUPLING: INSERT: O-RING: APPROVALS US: CANADA:	GOLD PLATED COPPER ALLOY GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED C-UL LISTED					DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY
	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD: COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS:	GOLD PLATED COPPER ALLOY GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED YES		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS	600V	DIMENSIONS ARE IN INCHES	DRAWN DATE CHECKED BY
	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD: COUPLING: INSERT: O-RING: APPROVALS US: CANADA:	GOLD PLATED COPPER ALLOY GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED C-UL LISTED		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	AMPS	8A	DIMENSIONS ARE IN INCHES AND [MM] MATERIAL	DRAWN DATE CHECKED BY CHECK DATE
•	CONTACTS: CABLE: STYLE: AWG: JACKET: VOLTAGE: SHIELD: COUPLING: INSERT: O-RING: APPROVALS US: CANADA: ROHS:	GOLD PLATED COPPER ALLOY GOLD PLATED COPPER ALLOY STOOW 16 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED YES		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF			DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY CHECK DATE

								_
MIN	1-5F	P-3A	\	36"	[0.9n	n]	YES	
MIN	1-5F	P-6A		72"	[1.8n	n]	YES	-
MIN	1-5F	P-12	Α	144"	[3.71	n]	YES	
MIN	1-5F	P-15	Α	180"	[4.6	n]	NO	
MIN	MIN-5FP-20A			240"	[6.1	n]	YES	
MIN	1-5F	P-30	Α	360"	[9.1	n]	YES	В
MIN	1-5F	P-40	Α	480"	[12.2	m]	NO	
MIN	1-5F	P-50	Α	600"	[15.2	m]	NO	
MIN	1-5F	P-60	Α	720"	[18.3	m]	NO	
MIN	1-5F	P-10	0A	1200"	' [30.5	5m]	NO	_
	-	-	-	NOT BEI NUM OF				_
DM 4/2023		MEN	ICON	1 COI	RPOF	RATIO	NC	
IJH 5/2023	TITLE	:						A
	size B	DWG.		N-5FP-	ZZA		rev B	_
	SCAL	E: 1:1	WEIGH	_	•	SHEE	[] OF]	-
	2					1		

С

STD?

L

1

P/N