PIN				6		5	4		3			2
	# COLO	R										
1	WHITE											
^D 2	RED											
3	GREE	N/YELLOW										
4	ORAN	GE		I								
5	BLAC	К				L						
C					[7.4] Ø.29				[38] 1.5		P/N MIN	-5FPX-3-R
					ψ . ${\it Z}$ /						MIN	-5FPX-6-R
->							_				MIN	-5FPX-12-I
												•••••
											МЛИ	5EDV 15 0
												-5FPX-15-
												-5FPX-15-l -5FPX-20-l
	ALS										MIN	
BODY:		YELLOW PVC GOLD PLATED COPPER A	ALLOY								MIN MIN	-5FPX-20-l -5FPX-30-l
BODY: CONTAC			ALLOY								MIN MIN	-5FPX-20-l
BODY:		GOLD PLATED COPPER	ALLOY			, , , (A		MIN MIN MIN	-5FPX-20-l -5FPX-30-l
BODY: CONTAC	CTS: STYLE:	GOLD PLATED COPPER	ALLOY				H		[25]		MIN MIN MIN MIN	-5FPX-20- -5FPX-30- -5FPX-40- -5FPX-50-
BODY: CONTAC	CTS: STYLE: AWG: JACKET:	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC	ALLOY						[25] 1.0		MIN MIN MIN MIN	-5FPX-20-l -5FPX-30-l -5FPX-40-l
BODY: CONTAC	CTS: STYLE: AWG: JACKET: VOLTAGE:	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V	ALLOY				H A		[25] 1.0		MIN MIN MIN MIN	-5FPX-20-f -5FPX-30-f -5FPX-40-f -5FPX-50-f -5FPX-60-f
BODY: CONTAC CABLE:	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD:	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO	ALLOY				H A		[25] 1.0		MIN MIN MIN MIN MIN	-5FPX-20-F -5FPX-30-F -5FPX-40-F -5FPX-50-F -5FPX-60-F -5FPX-100
	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD:	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS	ALLOY				H A		[25] 1.0		MIN MIN MIN MIN MIN	-5FPX-20-F -5FPX-30-F -5FPX-40-F -5FPX-50-F -5FPX-60-F -5FPX-100 RTS LISTED A
	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG:	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC	ALLOY			7/8-16UN2B			<u> </u>		MIN MIN MIN MIN MIN	-5FPX-20-F -5FPX-30-F -5FPX-40-F -5FPX-50-F -5FPX-60-F -5FPX-100
	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG:	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS				7/8-16UN2B FEMALE THR	H A READ		UNLESS OTHERWISE SPECIFIED		MIN MIN MIN MIN MIN PAR	-5FPX-20-F -5FPX-30-F -5FPX-40-F -5FPX-50-F -5FPX-60-F -5FPX-100 RTS LISTED A
COUPLIN INSERT: O-RING:	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG:	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC				7/8-16UN2B FEMALE THE	H A READ		<u> </u>	DRAWN DATE 11	MIN MIN MIN MIN MIN PAF	-5FPX-20-I -5FPX-30-I -5FPX-40-I -5FPX-50-I -5FPX-60-I -5FPX-100 RTS LISTED A MAY REQU MENCO
COUPLIN INSERT: O-RING:	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG: :	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A				7/8-16UN2B FEMALE THR	H F READ		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN DATE 11/ CHECKED BY	MIN MIN MIN MIN MIN PAF	-5FPX-20-1 -5FPX-30-1 -5FPX-40-1 -5FPX-50-1 -5FPX-60-1 -5FPX-100 RTS LISTED A MAY REQU
COUPLIN INSERT: O-RING: APPROV US:	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG: : /ALS	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A				7/8-16UN2B FEMALE THR	H A READ		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN DATE 11/ CHECKED BY	MIN MIN MIN MIN MIN PAF	-5FPX-20-I -5FPX-30-I -5FPX-40-I -5FPX-50-I -5FPX-60-I -5FPX-100 RTS LISTED A MAY REQU MENCO
COUPLIN INSERT: O-RING: APPROV US: CANADA	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG: : /ALS	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED				7/8-16UN2B FEMALE THR	READ/		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN DATE 11/ CHECKED BY	MIN MIN MIN MIN MIN PAF	-5FPX-20-I -5FPX-30-I -5FPX-40-I -5FPX-50-I -5FPX-60-I -5FPX-100 RTS LISTED A MAY REQU MENCO
COUPLIN CONTAC CABLE: CABLE: COUPLIN INSERT: O-RING: APPROV US: CANAD/ ROHS:	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG: : /ALS	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED YES				FEMALE THR	read/ Volts	300∨	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 11/ CHECKED BY	MIN MIN MIN MIN MIN MIN PAF	-5FPX-20-I -5FPX-30-I -5FPX-40-I -5FPX-50-I -5FPX-60-I -5FPX-100 RTS LISTED A MAY REQU MENCO
COUPLIN INSERT: O-RING: APPROV US: CANADA	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG: : /ALS	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED				FEMALE THR PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	READ/	300V 5.5A	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN DATE 117 CHECKED BY CHECK DATE 117	MIN MIN MIN MIN MIN MIN PAF	-5FPX-20-F -5FPX-30-F -5FPX-40-F -5FPX-50-F -5FPX-60-F -5FPX-100 RTS LISTED A MAY REQU MENCO TITLE:
COUPLIN CONTAC CABLE: CABLE: COUPLIN INSERT: O-RING: APPROV US: CANAD/ ROHS:	CTS: STYLE: AWG: JACKET: VOLTAGE: SHIELD: NG: : /ALS A: : :	GOLD PLATED COPPER A AWM 18 AWG YELLOW PVC 600V NO NICKEL PLATED BRASS YELLOW PVC N/A UL LISTED C-UL LISTED YES				FEMALE THR PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	read/ Volts		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 117 CHECKED BY CHECK DATE 117	MIN MIN MIN MIN MIN MIN PAF	-5FPX-20-I -5FPX-30-I -5FPX-40-I -5FPX-50-I -5FPX-60-I -5FPX-100 RTS LISTED A MAY REQU MENCO

		P/N			L	STD?	С	
		MIN	I-5FPX-3-	R 36	" [0.9m]	YES	-	
		MIN	I-5FPX-6-	R 72	" [1.8m]	YES		
		MIN	I-5FPX-12	2-R 14	4" [3.7m] YES	-	
		MIN	I-5FPX-15	5-R 18		-		
		MIN	I-5FPX-20		- D" [6.1m	-		
		MIN	I-5FPX-30		-)" [9.1m		E	
		MIN	I-5FPX-40)-R 480	- " [12.2m	n] NO		
		MIN	I-5FPX-50)-R 600	- " [15.2m	n] NO		
		MIN	I-5FPX-60)-R 720	" [18.3m	n] NO		
		MIN	I-5FPX-10)0-F 120	_ 0" [30.5r	n] NO	_	
		PA	RTS LISTED MAY REG					
SE SPECIFIED:	DRAWN BY	ADM	MENCOM CORPORATION					
n inches	DRAWN DATE	11/14/2023	3					
	CHECKED BY	JJH	TITLE:					
	CHECK DATE	11/15/2023	-				A	
	COMMENTS:		SIZE DWG.	NO.		REV	-	
			B	MIN-5F	PX-ZZ-R	B		
DRAWING	-		SCALE: 1:1	WEIGHT:		Sheet 1 of 1	1	
3			2		1			