	8		7	6	5	2	4	3	
PIN# 0	COLOF	२							
1 \	WHITE		_						
	RED								
		V YELLOW							
	ORANG								
	BLACK								
	BLUE	•							
			L .	FLAT		6 UN2A		KEY C SHOV FLAT	ORIE VN F ON
									[
SHELL: CONTACTS:		CLEAR ANODIZED AL GOLD PLATED COPPI		[3.2]	[19.7]				[
SHELL: CONTACTS:									
SHELL: CONTACTS:	STYLE:	GOLD PLATED COPPI		[3.2]	[19.7]			L	28.6
SHELL: CONTACTS: WIRES:	STYLE:	GOLD PLATED COPPI UL 1015 16 AWG		[3.2]	[19.7]			L	28.6
	STYLE: AWG:	GOLD PLATED COPPI UL 1015 16 AWG PVC		[3.2]	[19.7]			L	28.6
SHELL: CONTACTS: WIRES: J	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC		[3.2]	[19.7]			L	28.6
SHELL: CONTACTS: WIRES: J VC	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC 600V		[3.2]	[19.7]			Ģ	28.6 2 1.1
SHELL: CONTACTS: WIRES: J VC NSERT: GASKET:	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC 600V YELLOW PVC		[3.2]	[19.7]			L	28.0 01.
SHELL: CONTACTS: WIRES: J VC INSERT:	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC 600V YELLOW PVC NBR		[3.2]	[19.7]			Ģ	28.6 21.1
SHELL: CONTACTS: WIRES: J VC INSERT: GASKET: NUT:	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC 600V YELLOW PVC NBR		[3.2]	[19.7]			UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	28.6 21.1 Drai Drai Cheu
SHELL: CONTACTS: WIRES: J VC INSERT: GASKET: NUT: APPROVALS	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC 600V YELLOW PVC NBR NICKEL PLATED BRAS		[3.2]	[19.7]			UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	28.6 21.1 Dra Dra CHE
SHELL: CONTACTS: WIRES: J VC INSERT: GASKET: NUT: APPROVALS US:	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC 600V YELLOW PVC NBR NICKEL PLATED BRAS		[3.2]	[19.7] .78	VOLTS	6001/	UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	28.6 0 1.1 Dra Dra CHE
SHELL: CONTACTS: WIRES: J VC INSERT: GASKET: NUT: APPROVALS US: CANADA:	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC 600V YELLOW PVC NBR NICKEL PLATED BRAS UL LISTED C-UL LISTED		[3.2]	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	VOLTS	600V 8A	UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	28.6 21.1 Dra Dra CHE
SHELL: CONTACTS: WIRES: J VC INSERT: GASKET: NUT: APPROVALS US: CANADA: ROHS:	STYLE: AWG: JACKET: DLTAGE:	GOLD PLATED COPPI UL 1015 16 AWG PVC 600V YELLOW PVC NBR NICKEL PLATED BRAS UL LISTED C-UL LISTED YES		[3.2]	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	AMPS	600V 8A 105°C	UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM]	28.6 21.1 DRAI CHEC CO

			M	N-6FR-10	-RM	120"	[3m]	ŀ
			О	THER LENG PLEASE CO				
	ADM							
	12/19/2023							
	JJH	TITLE	:					
	01/11/2024							
rs:		SIZE	DWG.	NO.			REV	-
		B		MIN-6FR	-ZZ-R	Μ	В	
		SCAL	E: 2:1	WEIGHT:		SHEE	T 1 OF 1	
		2				1		

 P/N
 L

 MIN-6FR-1-RM
 12" [0.3m]

 MIN-6FR-2-RM
 24" [0.6m]

 MIN-6FR-3-RM
 39" [1.0m]

 MIN-6FR-6-RM
 79" [2.0m]

 MIN-6FR-10-RM
 120" [3m]

ATION AS ATIVE TO ELL D

С

В

1