	0	/	6	5	4		3		2	1
PIN#	COLOR			· · · · · · · · · · · · · · · · · · ·						
1 \	WHITE									
2 F	RED									
3 (GREEN / YELLOW									
4 (ORANGE									
5 I	BLACK									
	BLUE									
0										
		1/2-14	4 NPT		I 6 UN2A			[25.4] 1.00	TABL P/N MIN-6MR-1	E A L 12" [0.3M]
MATERIALS	3	[10.:		.55					MIN-6MR-2	
HELL:	ANODIZED ALUMI	.42 UM							MIN-6MR-3	36" [0.9M
HELL: ONTACTS	ANODIZED ALUMI	.42 UM							MIN-6MR-3 MIN-6MR-4	36" [0.9M 48" [1.2M
HELL: ONTACTS	ANODIZED ALUMI	.42 UM		.55					MIN-6MR-3 MIN-6MR-4 MIN-6MR-6	36" [0.9M 48" [1.2M 72" [1.8M
HELL: CONTACTS /IRES:	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG	.42 UM		AN O-RING AND L					MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M
HELL: :ONTACTS /IRES:	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC	.42 UM		.55					MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M 180" [4.6M
HELL: CONTACTS VIRES: V	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V	.42 UM		AN O-RING AND L					MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20	36" [0.9M] 48" [1.2M] 72" [1.8M] 120" [3.0M] 180" [4.6M] 240" [6.1M]
HELL: CONTACTS /IRES: VIRES: V	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V YELLOW PVC	.42 UM		AN O-RING AND L					MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M 180" [4.6M 240" [6.1M ARE AVAILABLE
HELL: ONTACTS 'IRES: V SERT: -RING:	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V	.42 UM		AN O-RING AND L				D: DRAWN BY ADM	MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20 OTHER LENGTHS PLEASE CONST	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M 180" [4.6M 240" [6.1M ARE AVAILABLI JLT FACTORY
HELL: ONTACTS /IRES: /IRES: V ISERT: -RING: UT:	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V YELLOW PVC NBR ZINC PLATED STEEL	.42 UM		AN O-RING AND L			UNLESS OTHERWISE SPECIFIER DIMENSIONS ARE IN INCHES	DRAWN DATE 01/10/202	MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20 OTHER LENGTHS PLEASE CONST	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M 180" [4.6M 240" [6.1M ARE AVAILABLE JLT FACTORY
HELL: CONTACTS /IRES: /IRES: V ISERT: -RING: UT: PPROVALS	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V VELLOW PVC NBR ZINC PLATED STEEL	.42 UM		AN O-RING AND L			NGER.	DRAWN DATE 01/10/202 CHECKED BY JJH	MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20 OTHER LENGTHS PLEASE CONST	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M 180" [4.6M 240" [6.1M ARE AVAILABLE JLT FACTORY
HELL: CONTACTS /IRES: /IRES: V ISERT: -RING: UT: PPROVAL: S:	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V YELLOW PVC NBR ZINC PLATED STEEL	.42 UM		AN O-RING AND L			UNLESS OTHERWISE SPECIFIER DIMENSIONS ARE IN INCHES	DRAWN DATE 01/10/202	MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20 OTHER LENGTHS PLEASE CONST	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M 180" [4.6M 240" [6.1M ARE AVAILABLE JLT FACTORY PORATION
HELL: CONTACTS VIRES: VIRES: V NSERT: D-RING: UT: NPPROVALS S: CANADA:	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V YELLOW PVC NBR ZINC PLATED STEEL S. UL LISTED C-UL LISTED	.42 UM		AN O-RING AND L ON LENGTHS OF 2	4'' [0.6M] /	AND LOI	UNLESS OTHERWISE SPECIFIER DIMENSIONS ARE IN INCHES	DRAWN DATE 01/10/202 CHECKED BY JJH	MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20 OTHER LENGTHS PLEASE CONST	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M 180" [4.6M 240" [6.1M ARE AVAILABLE JLT FACTORY PORATION
HELL: CONTACTS VIRES: VIRES: VIRES: V NSERT: D-RING: UT: V S: CANADA: OHS:	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V /OLTAGE: 600V /OLTAGE: 500V /OLTAGE: 500	.42 UM		AN O-RING AND L ON LENGTHS OF 2	4'' [0.6M] / VOLTS	101 DNA	UNLESS OTHERWISE SPECIFIEI DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 01/10/202 CHECKED BY JJH	MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20 OTHER LENGTHS PLEASE CONST MENCOM CORF	36" [0.9M 48" [1.2M 72" [1.8M 120" [3.0M 180" [4.6M 240" [6.1M ARE AVAILABLE JLT FACTORY PORATION
	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V /OLTAGE: 600V /OLTAGE: 500V /OLTAGE: 500	.42 UM		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	4'' [0.6M] / VOLTS AMPS	101 DNA 600V 8A	UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 01/10/202 CHECKED BY JJH CHECK DATE 01/12/202	MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20 OTHER LENGTHS PLEASE CONST MENCOM CORF TITLE: 4 5 PL MAL RCP	36" [0.9M] 48" [1.2M] 72" [1.8M] 120" [3.0M 180" [4.6M 240" [6.1M ARE AVAILABLE JLT FACTORY PORATION 16AWG
HELL: CONTACTS VIRES: VIRES: V NSERT: D-RING: UT: NPPROVALS S: CANADA: OHS:	ANODIZED ALUMIN S: GOLD PLATED CON STYLE: UL 1015 AWG: 16 AWG JACKET: PVC /OLTAGE: 600V /OLTAGE: 600V /OLTAGE: 500V /OLTAGE: 500	.42 UM		AN O-RING AND L ON LENGTHS OF 2	4'' [0.6M] / VOLTS	101 DNA	UNLESS OTHERWISE SPECIFIEI DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE 01/10/202 CHECKED BY JJH CHECK DATE 01/12/202	MIN-6MR-3 MIN-6MR-4 MIN-6MR-6 MIN-6MR-10 MIN-6MR-15 MIN-6MR-20 OTHER LENGTHS PLEASE CONST MENCOM CORF	JLT FACTORY PORATION 16AWG REV