| MALE | WIRING | FEMALE |
|---|---|---|
| PIN # | | PIN # |
| 1 | --------- | 1 |
| 2 | --------- | 2 |
| 3 | --------- | 3 |
| 4 | --------- | 4 |
| 5 | --------- | 5 |
| 6 | --------- | 6 |
| 7 | --------- | 7 |




| MATERIALS | |
|---|---|
| BODY: | BLACK PVC |
| CONTACTS: | GOLD PLATED COPPER ALLOY |
| CABLE: | |
| STYLE: | TC-ER |
| AWG: | 16 AWG |
| JACKET: | BLACK PVC |
| VOLTAGE: | 600V |
| SHIELD: | NO |
| COUPLING: | NICKEL PLATED BRASS |
| INSERT: | YELLOW PVC |
| O-RING: | N/A |
| | |
| APPROVALS | |
| US: | UL LISTED |
| CANADA: | C-UL LISTED |
| ROHS: | YES |
| CE & UKCA: | YES |
| | |
| RATINGS | |
| PROTECTION CLASS: | UL TYPE 4 & 12, IEC IP69 |

| TABLE A | | |
|---|---|---|
| P/N | L | STD? |
| MIN-7MFP-3-C011 | 36" [0.9M] | YES |
| MIN-7MFP-6-C011 | 72" [1.8M] | YES |
| MIN-7MFP-12-C011 | 144" [3.7M] | YES |
| MIN-7MFP-15-C011 | 180" [4.6M] | NO |
| MIN-7MFP-20-C011 | 240" [6.1M] | YES |
| MIN-7MFP-30-C011 | 360" [9.1M] | YES |
| MIN-7MFP-40-C011 | 480" [12.2M] | NO |
| MIN-7MFP-50-C011 | 600" [15.2M] | NO |
| MIN-7MFP-60-C011 | 720" [18.3M] | NO |
| MIN-7MFP-100-C011 | 1200" [30.5M] | NO |

PARTS LISTED AS NOT BEING STANDARD
MAY HAVE MINIMUM ORDER QUANTITIES

**PROPRIETARY AND CONFIDENTIAL**
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

| | |
|---|---|
| VOLTS | 600V |
| AMPS | 8A |
| TEMP: | 105°C |

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

| | |
|---|---|
| DRAWN BY | GO |
| DRAWN DATE | 03/06/2024 |
| CHECKED BY | JJH |
| CHECK DATE | 03/07/2024 |

COMMENTS:

MENCOM CORPORATION

TITLE:

| SIZE | DWG. NO. | REV |
|---|---|---|
| B | MIN-7MFP-ZZ-C011 | B |

SCALE: 1:2 | WEIGHT: | SHEET 1 OF 1