| PIN # | WIRING | PIN # |
|---|---|---|
| | | |
| 1 | --------- | 1 |
| 2 | --------- | 2 |
| 3 | --------- | 3 |
| 4 | --------- | 4 |
| 5 | --------- | 5 |
| | ETC. | |
| 9 | --------- | 9 |




| TABLE A | | |
|---|---|---|
| P/N | L | STD? |
| | | |
| MIN-9MFPX-3 | 36" [0.9m] | YES |
| MIN-9MFPX-6 | 72" [1.8m] | YES |
| MIN-9MFPX-10 | 120" [3.8m] | YES |
| MIN-9MFPX-12 | 144" [3.6m] | YES |
| MIN-9MFPX-20 | 240" [6.1m] | YES |
| MIN-9MFPX-30 | 360" [9.1m] | YES |
| MIN-9MFPX-40 | 480" [12.2m] | NO |
| MIN-9MFPX-50 | 600" [15.2m] | NO |
| MIN-9MFPX-60 | 720" [18.3m] | NO |

PARTS LISTED AS NOT BEING STANDARD
MAY HAVE MINIMUM ORDER QUANTITIES

| MATERIALS | |
|---|---|
| BODY: | YELLOW PVC |
| CONTACTS: | GOLD PLATED COPPER ALLOY |
| CABLE: | |
| STYLE: | AWM |
| AWG: | 18 AWG |
| JACKET: | YELLOW PVC |
| VOLTAGE: | 300V |
| SHIELD: | NO |
| COUPLING: | NICKEL PLATED BRASS |
| INSERT: | YELLOW PVC |
| O-RING: | N/A |
| | |
| APPROVALS | |
| US: | UL LISTED |
| CANADA: | C-UL LISTED |
| ROHS: | YES |
| CE & UKCA: | YES |
| | |
| RATINGS | |
| PROTECTION CLASS: | UL TYPE 4 & 12, IEC IP69 |


**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.


| | |
|---|---|
| VOLTS | 300V |
| AMPS | 4A |
| TEMP: | 105°C |

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

| | |
|---|---|
| DRAWN BY | ADM |
| DRAWN DATE | 02/01/2024 |
| CHECKED BY | JJH |
| CHECK DATE | 02/01/2024 |

COMMENTS:

MENCOM CORPORATION

TITLE:

| SIZE | DWG. NO. | REV |
|---|---|---|
| B | MIN-9MFPX-ZZ | C |

SCALE: 1:1 | WEIGHT: | SHEET 1 OF 1