	8			6	5	4		3	
	PIN #	COLOR						REV.	D
	1 8	BROWN						A	RE
	2 \	VHITE							
	3 E	BLUE							
	4 E	BLACK							
	[25.4] 1.0	200		-7/8-16UN2B FEMALE THREAD		– L – 2-14 NPT 0.3] 41			
B IN C W O	MATERIALS BODY: NSERT: CONTACTS WIRES: D-RING: LOCK-NUT:	ANODIZED BLACK PV	C ED COPPER ALLOY 9 18AWG		O-Ring and Locknu engths of 19" and l	t are includ onger.	U	INLESS OTHERWISE SPECIFIED: IMENSIONS ARE IN INCHES IND [MM]	DRAWN CHECKED ENG APPR
B IN C W O L	BODY: NSERT: CONTACTS WIRES: D-RING:	ANODIZED BLACK PV GOLD PLA UL1007/156 NBR ZINC PLAT	C ED COPPER ALLOY 9 18AWG		PROPRIETARY AND CONFIDENTIAL			imensions are in inches nd [mm]	DRAWN CHECKED ENG APPR. MFG APPR. Q.A.
B IN C W O L	BODY: NSERT: CONTACTS VIRES: D-RING: LOCK-NUT:	ANODIZED BLACK PV GOLD PLA UL1007/156 NBR ZINC PLAT	C ED COPPER ALLOY 9 18AWG		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	VOLTS 30		IMENSIONS ARE IN INCHES	DRAWN CHECKED ENG APPR. MFG APPR. Q.A.
B IN C W O L C	BODY: NSERT: CONTACTS VIRES: D-RING: LOCK-NUT:	ANODIZED BLACK PV GOLD PLA UL1007/156 NBR ZINC PLAT	C ED COPPER ALLOY 9 18AWG ED STEEL		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS 30 AMPS 5.	00V 5A	imensions are in inches nd [mm]	DRAWN CHECKED ENG APPR. MFG APPR.

escriptio	N	DATE		APPRO	VED
RAWN IN	SW	10/6/2	004		
					D
	SLE A				C
P/N				L	
MINC	C-4FR-1-18		12	2" [0.3r	n]
MINC	MINC-4FR-0.5M		19	Ə" [0.5r	n]
MINC	MINC-4FR-0.6M		24	4" [0.6r	n]
MINC	-4FR-1M-1	8 7 8 1		0" [1m] B
MINC	-4FR-2M-1			'9" [2m]
MINC	C-4FR-3M-1			18" [3n	n]
MINC	C-4FR-5M-1			97" [5n	n]
MINC	MINC-4FR-6M-1		23	36" [6n	n]
MINC	-4FR-10M-	·18	39	93" [10r	n]
NAME BEM	MENCC	м со	RPO	RATIO	1
	TITLE:				A
3:		о. NC-4FR IGHT:	2-ZZ-1	8 SHEET 1	REV A OF 1

REVISIONS