



FEM	WIRING	MALE
PIN #		PIN #
1	----	1
2	----	2
3	----	3
4	----	4

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	DRAWN IN SW	3/5/2014	RSC



NOTE: TUBING WILL NOT BE OVERMOLDED. EXPOSED CABLE ON ONE END COULD BE AS HIGH AS 0.25", BUT THIS MEANS THE CABLE WILL BE BUTTING UP AGAINST THE CONNECTOR ON THE OTHER END. IF TUBING IS CENTERED BETWEEN CONNECTORS, THE MAXIMUM EXPOSED CABLE WILL BE 0.125".

TABLE A		
P/N	L	STD?
MINCWF-4MFRPX-1M-B-A50	40" [1m]	YES
MINCWF-4MFRPX-2M-B-A50	79" [2m]	YES
MINCWF-4MFRPX-3M-B-A50	118" [3m]	NO
MINCWF-4MFRPX-4M-B-A50	157" [4m]	YES
MINCWF-4MFRPX-5M-B-A50	197" [5m]	NO
MINCWF-4MFRPX-6M-B-A50	236" [6m]	YES
MINCWF-4MFRPX-8M-B-A50	315" [8m]	NO
MINCWF-4MFRPX-10M-B-A50	393" [10m]	YES
MINCWF-4MFRPX-15M-B-A50	590" [15m]	NO
MINCWF-4MFRPX-20M-B-A50	786" [20m]	NO

PARTS LISTED AS NOT BEING STANDARD
MAY HAVE MINIMUM ORDER QUANTITIES

MATERIALS	
BODY:	BLACK TPE
INSERT:	BLACK TPE
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	18/4 CONTINUOUS FLEX EURO CC BLACK TPE JACKET. 20MM FLEXES, MIN BEND RADIUS IS 10x CABLE OD
COUPLING:	NICKEL PLATED BRASS
TUBING:	SILICONE TUBE NATURAL 50A DUROMETER

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS	300V
AMPS	5.5A
TEMP	105°C
SPECIFICATIONS	

UNLESS OTHERWISE SPECIFIED:		NAME
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN	JJH
	CHECKED	
	ENG APPR.	
	MFG APPR.	
	Q.A.	
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE:		
4 PL HI FLX EURO M- RA F EXT PLG R/A 18AWG ARMRD		
SIZE	DWG. NO.	REV
B	MINCWF-4MFRPX-ZZ-B-A50	A
SCALE: 1:1	WEIGHT:	SHEET 1 OF 1