		8		7	6		5	4	Ļ	3		
	MIN	WIRING										
	PIN #		PIN#									
	1		3									
D	2		4									
	3		1									
		[o -	.7				[]					
		[25 1.0)				[70] 2.8			_		
		00000	2000		AA. I						-	
С	d			L .							8	کر مر
-	Ĭ		20				0.6				Ĵ 🛛 🟅	
	ş		D. ////	l k			AD					
	S			F								
->			Nov S								200	
					\7/8	3-16UN2A						
В												
										UNLESS OTHERWISE SPECIFIED:	DRAWN BY	
										DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE CHECKED BY	05
А	MATERIALS											05
	BODY:						PROPRIETARY AND CONFIDENTIAL	VOLTS	300V			
	COUPLINGS: NICKEL PLATED BRASS					HE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	AMPS	4A	MATERIAL	COMMENTS:		
	CONTACTS:	CONTACTS: GOLD PLATED COPPER ALLOY MDC INSULATOR: POLYAMIDE				MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE	TEMP:	105°C	FINISH	_		
	O-RING:	NBR					WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.		100 C	DO NOT SCALE DRAWING		
L		8		7	6		5	4	1	3		

