	8	1	7	6	5	4	3	I	2	1
	PIN# COL	OR			Y					
-	1 GRE	EN/YELLOW								
-	2 BLA									
D	3 WHI									C
				L						
						7.0.1				
				1/2-14 NF	νт		SUN2B LE THREAD			
				1/2-14 11						
С								≜		C
				,						
								[25]		
							<mark>3 2⊕/ /</mark> /////	1.0	P/N	L
			\`\`\`\`\`\`\`\`\`\`\`\`\`\`\`\`\`\`\`	$\mathbf{\hat{k}}$						-
									MINH-3FR-1	12" [0.3M]
В				[10.3]	[13.3]				MINH-3FR-0.5M	
				.41	.52				MINH-3FR-0.6M	24" [0.6M]
-	MATERIALS								MINH-3FR-1M	40" [1m]
-	SHELL: CONTACTS:	CLEAR ANODIZED A GOLD PLATED COPF							MINH-3FR-2M	79" [2m]
-	WIRES:								MINH-3FR-3M	117" [3m]
-		IYLE: UL 1015 WG: 14 AWG			AN O-RING AND LOCKNUT ARE INCLUDED					
		CKET: PVC			ON LENGTHS OF 24" [0.6M] AND LONGER.					157" [4m]
F	VOLT									197" [5m]
	INSERT: O-RING:	YELLOW PVC NBR		OTHER LENGTHS ARE AVAILABLE PLEASE CONSULT FACTORY						
-	NUT:	ZINC PLATED STEEL					UNLESS OTHERWISE SPECIFIED:	DRAWN BY ADM		
ļ					DIMENSIONS ARE IN INCHES DRAWN DATE 03/14/2024 AND [MM]			DRAWN DATE 03/14/2024		JKAIION
Α	PPROVALS							CHECKED BY JJH CHECK DATE 03/15/2024	TLE:	, A A A A A A A A A A A A A A A A A A A
-	CANADA: C-UL LISTED CHECK DATE 05/15/2024								,	
-	ROHS:	YES			PROPRIETARY AND CONFIDENTIAL	VOLTS 600V				
ļ	CE & UKCA:	YES			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	AMPS 18A	MATERIAL		E DWG. NO.	REV
+	RATINGS				MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF	TEMP: 105°C	FINISH		MINH-3FR-Z	Z B
-		ASS: UL TYPE 4 & 12, IEC I	IP69		MITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.		DO NOT SCALE DRAWING		ALE: 2:1 WEIGHT:	SHEET 1 OF 1
	8		7	6	5	4	3		2	1