



M32x1.5
FEMALE
THREADED
OPENING

MHO-16.32

CNEM-16T

CNEF-16T

CHI-16

PANEL CUTOUT

[4.5]
Ø.18
4X

Certifications	
(under individual component part numbers)	
US:	UL Recognized
Canada:	C-UL Recognized
Europe:	CE
China:	CCC

MATERIALS	
BODY:	EPOXY COATED DIE CAST ALUMINUM
GASKET:	THERMOPLASTIC ELASTOMER
HANDLE:	POLYAMIDE
LEVERS:	STAINLESS STEEL
INSERTS:	GLASS REINFORCED THERMOPLASTIC
CONTACTS:	SILVER PLATED COPPER ALLOY

SUGGESTED CABLE GLANDS FOR HOOD		
P/N	MATERIAL	CLAMPING RANGE
MCG-M32	NICKEL PLATED BRASS	12 - 21mm
PCGU-M32	GRAY POLYAMIDE	12 - 21mm

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

Environmental Ratings:

NEMA / UL: 4, 4X, 12

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES
AND [MM]

MATERIAL

FINISH

DO NOT SCALE DRAWING

DRAWN BY	DCG
DRAWN DATE	05/12/2017
CHECKED BY	DWM
CHECK DATE	05/12/2017

COMMENTS:

MENCOM CORPORATION

TITLE:
16PL M-F INS 2 LV BS M32
RA HD

SIZE	DWG. NO.	REV
B	MNDS-16IO32	A
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1