



B	MATERIALS:	
	BODY:	POLYAMIDE
	COUPLING:	NICKEL PLATED BRASS
	CONTACTS:	GOLD PLATED COPPER ALLOY
	GROMMET:	NBR
	O-RING:	NBR
	SPECIFICATIONS:	
A	WIRE RANGE:	20-26AWG [0.5 - 0.14sqmm]
	CABLE RANGE:	0.118 - 0.197 [3 - 5mm]
	CONNECTION:	SCREW TERMINALS
	VOLTS:	30V
	AMPS:	3A
	SEAL:	IP67
	TEMP RANGE:	STATIC: -40°C - +85°C
		DYNAMIC: -20°C -+85°C

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	ADM	MENCOM CORPORATION		
	DRAWN DATE	11/29/2023			
	CHECKED BY	ADM	TITLE: 3 PL SCRW TERM FW NAN		
	CHECK DATE	11/29/2023			
MATERIAL	COMMENTS:		SIZE	DWG. NO.	REV
FINISH			B	NAN-T-3FP-FW-ST	C
DO NOT SCALE DRAWING			SCALE: 3:1	WEIGHT:	SHEET 1 OF 1