[44] 1.73 0.87 -PG11 THREAD [15] .58 NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL. CRUSH RIBS ON THE UNDERSIDE OF HEX WILL PROVIDE THE SEAL. SEALING RANGE: .118" - .275" (3 - 7MM) **SEAL RATED TO: IP68 MATERIALS** UNLESS OTHERWISE SPECIFIED: DRAWN BY MENCOM CORPORATION DRAWN DATE 06/29/2022 DIMENSIONS ARE IN MM TOLERANCES:
FRACTIONAL±1/64
ANGULAR: MACH±3° BEND ±5°
ONE PLACE DECIMAL ±.2
TWO PLACE DECIMAL ±.1

DIRAWN DATE
00/27/2022
CHECKED BY
ADM
CHECK DATE
06/29/2022 TITLE: **BODY: BLACK POLYAMIDE GROMMET:** CR/NBR PLSTC CBL GLND PG11 **SPECIFICATIONS:** PROPRIETARY AND CONFIDENTIAL COMMENTS: THE INFORMATION CONTAINED IN THIS SIZE DWG. NO. REV DRAWING IS THE SOLE PROPERTY OF PCG-11RL-B MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF **TIGHTENING TORQUE: 3.75 Nm**

MENCOM CORPORATION IS

DO NOT SCALE DRAWING

3

PROHIBITED.

SCALE: 2:1

WEIGHT:

SHEET 1 OF 1

TEMPERATURE:

-20°C - +100°C