MULTIHOLE GROMMETT 3 HOLES EA WITH \emptyset [6] \emptyset .24 [47.5] MAX. 1.87 1.06 1/2-14 NPT 15] NO O-RING IS NECESSARY TO OBTAIN IP65 SEAL. CRUSH RIBS ON THE UNDERSIDE OF HEX WILL PROVIDE THE SEAL. 1/2" NPT LOCK-NUT ORDERED SEPARATELY, P/N 212PA SEALING RANGE: .216 - .256 (5.5 - 6.5MM) SEAL RATED TO: IP65 (WHEN ALL 3 HOLES ARE USED WITH APPROPRIATE DIAMETERS) **MATERIALS** UNLESS OTHERWISE SPECIFIED: DRAWN BY DCG MENCOM CORPORATION 06/29/2022 DIMENSIONS ARE IN INCHES DRAWN DATE TITLE: ADM **BODY: GRAY POLYAMIDE** 06/29/2022 CHECK DATE 1/2" CBL GLND 3X6 OPENINGS **GROMMET: TPE SPECIFICATIONS:** PROPRIETARY AND CONFIDENTIAL COMMENTS: THE INFORMATION CONTAINED IN THIS SIZE DWG. NO. REV DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY B PCG-1/2-3X6 TIGHTENING TORQUE: 5.0 Nm REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF

SCALE: 2:1

DO NOT SCALE DRAWING

WEIGHT:

SHEET 1 OF 1

-20°C - +100°C

TEMPERATURE: