



NO O-RING IS NECESSARY TO OBTAIN IP65 SEAL. CRUSH RIBS ON THE UNDERSIDE OF HEX WILL PROVIDE THE SEAL.

SEALING RANGE: Two ASI Cables
SEAL RATED TO: IP65

MATERIALS	
BODY:	BLACK POLYAMIDE
GROMMET:	TPE
SPECIFICATIONS:	
TIGHTENING TORQUE:	5.0 Nm
TEMPERATURE:	-20°C - +100°C

Lock-nut is not supplied with this part. To order a lock-nut please order 212PA/SW

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		DRAWN BY	JJH	MENCOM CORPORATION					
DIMENSIONS ARE IN MM TOLERANCES: FRACTIONAL ±1/64 ANGULAR: MACH ±3° BEND ±5° ONE PLACE DECIMAL ±.2 TWO PLACE DECIMAL ±.1		DRAWN DATE	09/11/2019				TITLE:		
		CHECKED BY							
		CHECK DATE							
		COMMENTS:		SIZE B					
MATERIAL									
FINISH									
DO NOT SCALE DRAWING									
				DWG. NO. PCG-12-B-2ASI		REV A			
				SCALE: 3:1		WEIGHT:			
						SHEET 1 OF 1			