



REVISIONS		
REV.	DESCRIPTION	DATE
A	REDRAWN IN SW	2/25/2005

MATERIALS	
BODY:	GRAY OR BLACK POLYAMIDE
GROMMET:	NEOPRENE

SPECIFICATIONS:	
TIGHTENING TORQUE:	3.75 Nm
TEMPERATURE:	-20°C - +100°C

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

SEAL RATED TO: IP68

NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL. CRUSH RIBS ON THE UNDERSIDE OF HEX WILL PROVIDE THE SEAL.

PART NUMBER	COLOR	SEALING RANGE
PCG-13.5	GRAY	6-12mm
PCG-13.5R	GRAY	5-9mm
PCG-13.5-B	BLACK	6-12mm
PCG-13.5R-B	BLACK	5-9mm

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES	NAME	MENCOM CORPORATION	
	DRAWN	BEM	
	CHECKED	TITLE:	
	ENG APPR.		
	MFG APPR.		
	Q.A.		
MATERIAL	COMMENTS:		
FINISH			
DO NOT SCALE DRAWING			
SPECIFICATIONS		SIZE	DWG. NO.
		B	PCG-13.5
		SCALE: 3:1	WEIGHT:
		SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.