[24] .94

[41]
1.61 max

M20x1.5 Thread

2M20PA LOCK NUT INCLUDED BUT NOT SHOWN

NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL. CRUSH RIBS ON THE UNDERSIDE OF HEX WILL PROVIDE THE SEAL.

BODY: GRAY POLYAMIDE
GROMMET: NEOPRENE

SPECIFICATIONS:

TIGHTENING TORQUE: 3.75 Nm
TEMPERATURE: -20°C - +100°C

APPROVALS:

US UL RECOGNIZED

C-UL RECOGNIZED

MATERIALS

CANADA

		PCG-M2 PCG-M2				GRAY BLACK	5-9mm 5-9mm	
	UNLESS OTHERWISE SPECIFIED:	DRAWN BY	DCG		۱ = N I ر	ICOM CORPORATIO		
	DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	04/11/2017	IVILIN		COMIC	VAIION	
		CHECKED BY	ADM	TITLE:	TITLE:			
		CHECK DATE	04/12/2017					
				PLSTC CBL GLND M20 THD 5-9MM				
PROPRIETARY AND CONFIDENTIAL		COMMENT	16.					
IHE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF	MATERIAL	COMINIEN	10.	SIZE [DWG.	WG. NO.		REV
	FINISH			SCALE: 3:1		PCG-M20RL		A
MENCOM CORPORATION IS PROHIBITED.	DO NOT SCALE DRAWING					WEIGHT:		SHEET 1 OF 1
4	3			2				1

PART NUMBER COLOR SEALING RANGE