


г	2	
F	<	

PROPERTIES				
EQUIPMENT GROUP		II		
CATEGORY / ZONE		2G and 2D	0 / 1, 2, 21, 22	2
TYPE OF PROTECTION:		Eex e , INCREASED SAFETY		
PROTECTION GRADE:		IP66		
CABLE INSTALLATION:		FIXED		
TEST STANDARD:		EN 50014 / EN 50019		
EC-TYPE CERTIFICATE:		PTB 99 A1	FEX 3128	
MATERIALS				
BODY:	BLA	CK POLY	AMIDE PA6	
SEALS:	INNE	INNER: TPE OUTER:		CR/NBR
DUST CAP:	POL	YETHYLE	NE PE-LD	
SPECIFICATIONS:				
TIGHTENING TORQUE:		2.7 Nm		
TEMPERATURE:		-30°C -	+70°C	
8			7	



5	4	3	I
PROHIBITED.	SPECIFICATIONS	DO NOT SCALE DRAWING	
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS		FINISH	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY	ī	MATERIAL	COMMENTS:
PROPRIETARY AND CONFIDENTIAL			Q.A.
			MFG APPR.
			ENG APPR.
			CHECKED
		DIMENSIONS ARE IN INCHES & [MM]	DRAWN
	_	UNLESS OTHERWISE SPECIFIED:	

I	2		1	
REVISIONS				
DESC	CRIPTION		DATE	
REDRA	WN IN SW		5/8/2007	
				D
	(1.5 Thread N 60423			C
MBER	COLOR	SEAL	ING RANG	B
120L-B	BLACK	5.5-1	3mm	_
S:	E DWG. NO.	CABLE C	GLAND M20	
SC	ALE: 2:1 WEIGHT:		SHEET 1 OF	1
			·	