



REVISIONS		
REV.	DESCRIPTION	DATE
A	REDRAWN IN SW	5/8/2007

NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL.  
CRUSH RIBS ON THE UNDERSIDE OF HEX WILL  
PROVIDE THE SEAL.

SEAL RATED TO: IP68

LOCK NUT INCLUDED BUT NOT SHOWN

MATERIALS	
BODY:	GRAY OR BLACK POLYAMIDE
GROMMET:	CR/NBR / OUTER PART TPE / INNER PART

SPECIFICATIONS:	
TIGHTENING TORQUE:	0.7 Nm
TEMPERATURE:	-20°C - +100°C

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

PART NUMBER	COLOR	SEALING RANGE
PCGU-M12	GRAY	2-5mm
PCGU-M12-B	BLACK	2-5mm

UNLESS OTHERWISE SPECIFIED:		NAME		MENCOM CORPORATION	
DIMENSIONS ARE IN INCHES		DRAWN	DWM		TITLE:  PLASTIC CABLE GLAND M12
		CHECKED			
		ENG APPR.			
		MFG APPR.			
		Q.A.			
MATERIAL	COMMENTS:		SIZE	DWG. NO.	REV
FINISH			<b>B</b>	PCGU-M12	<b>A</b>
DO NOT SCALE DRAWING			SCALE: 2:1	WEIGHT:	SHEET 1 OF 1

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.