



REVISIONS		
REV.	DESCRIPTION	DATE
A	REDRAWN IN SW	5/8/2007

NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL.
CRUSH RIBS ON THE UNDERSIDE OF HEX WILL
PROVIDE THE SEAL.

SEAL RATED TO: IP68

LOCK NUT INCLUDED BUT NOT SHOWN

MATERIALS	
BODY:	GRAY OR BLACK POLYAMIDE
GROMMET:	CR/NBR / INNER PART TPE / OUTER PART

SPECIFICATIONS:	
TIGHTENING TORQUE:	2.0 Nm
TEMPERATURE:	-20°C - +100°C

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

PART NUMBER	COLOR	SEALING RANGE
PCGU-M16	GRAY	3-10mm
PCGU-M16-B	BLACK	3-10mm

UNLESS OTHERWISE SPECIFIED:		NAME	MENCOM CORPORATION	
DIMENSIONS ARE IN INCHES	DRAWN	DWM	TITLE:	
	CHECKED		PLASTIC CABLE GLAND M16	
	ENG APPR.			
	MFG APPR.			
	Q.A.			
MATERIAL	COMMENTS:		SIZE	DWG. NO.
FINISH			B	PCGU-M16
DO NOT SCALE DRAWING			SCALE: 2:1	WEIGHT:
			SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.