


PIN #	COLOR
1	BLACK
2	GREEN/YELLOW
3	WHITE



MATERIALS	
BODY:	BLACK PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	
STYLE:	STOOW
AWG:	10 AWG
JACKET:	GRAY PVC
VOLTAGE:	600V
SHIELD:	NO
COUPLING:	NICKEL PLATED BRASS
INSERT:	BLACK PVC
RATINGS	
SCCR RATING:	65 kA Breakers and Fuses
RoHS COMPLIANT:	YES
PROTECTION:	IEC IP67
UL CATEGORY:	PVVA (US), PVVA7 (Canada)
U.S.:	UL 2237 LISTED, File E469485
CANADA:	C-UL 2237 LISTED, File E469485

CAUTION:
RISK OF ELECTRICAL SHOCK
DO NOT DISCONNECT UNDER LOAD

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.	VOLTS	600V
	AMPS	42A
	TEMP:	-40° to 90°C

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	ADM
	DRAWN DATE	02/16/2024
	CHECKED BY	JJH
	CHECK DATE	02/19/2024
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

P/N	L	STD?
PMIN-30MP-1M-R	40" [1m]	YES
PMIN-30MP-2M-R	79" [2m]	YES
PMIN-30MP-3M-R	117" [3m]	NO
PMIN-30MP-4M-R	157" [4m]	NO
PMIN-30MP-5M-R	197" [5m]	YES
PMIN-30MP-6M-R	236" [6m]	NO
PMIN-30MP-8M-R	315" [8m]	NO
PMIN-30MP-10M-R	393" [10m]	YES
PMIN-30MP-15M-R	590" [15M]	YES

PARTS LISTED AS NOT BEING STANDARD
MAY REQUIRE MINIMUM ORDERS
OTHER LENGTHS AVAILABLE,
PLEASE CONSULT FACTORY

MENCOM CORPORATION			
TITLE: 3 PL MAL R/A PLG PMIN 10AWG			
SIZE B	DWG. NO. PMIN-30MP-ZZ-R		REV C
SCALE: 1:1		WEIGHT:	SHEET 1 OF 1