



Voltage rating is 600V or the rating of the cable, whichever is less.

Connections made via  
screw terminal

MATERIALS:			
BODY:	BLACK POLYAMIDE		
CONTACTS:	GOLD PLATED COPPER ALLOY		
CABLE SEAL:	NBR		
INSERT:	PBT		
COUPLING:	NICKEL PLATED BRASS		
RATINGS:			
	AWG	CABLE RATED <75°C	CABLE RATED 75°C+
AMPS:	10AWG	35A	45A
	12AWG	28A	35A
	14AWG	24A	30A
VOLTS:	600VAC MAX		
CABLE RANGE:	10 AWG - 14AWG		
STOW, STOOW (US)	.530"-.576" (13-15mm) Gray Grommet		
	.542"-.707" (13-18mm) Black Grommet		
TC-ER (US)	.468"-.509" (12-13mm) Gray Grommet		
	.502"-.509" (12-13mm) Black Grommet		
SEOOW (US)	.516"-.630" (13-16mm) Gray Grommet		
	.516"-.7185" (13-18mm) Black Grommet		
STOW, STOOW (CN)	.542"-.707" (13-18mm) Black Grommet		
SEOOW (CN)	.516"-.718" (13-18mm) Black Grommet		
SCCR RATING:	65kA Breakers and Fuses		
RoHS COMPLIANT:	Yes		
PROTECTION:	IP67		
UL CATEGORY:	PVVA (US), PVVA7 (Canada)		
U.S.	UL 2237 LISTED, File E469485		
CANADA	C-UL 2237 LISTED, File E469485		

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		DRAWN BY		MENCOM CORPORATION					
DIMENSIONS ARE IN INCHES AND [MM]		DRAWN DATE	01/06/2021				TITLE:		
		CHECKED BY							
		CHECK DATE							
		COMMENTS:		A					
MATERIAL									
FINISH									
DO NOT SCALE DRAWING									
		SIZE	DWG. NO.		REV				
		B	PMIN-3FP-FW-R		A				
		SCALE: 1:1		WEIGHT:	SHEET 1 OF 1				