

	P/	'N				L			STD?
	PMIN-40MP-1M				40" [1m]			YES	
	PI	PMIN-40MP-2M PMIN-40MP-3M				79" [2m] 117" [3m]			YES NO
	P								
	P	MIN	-40M	P-41	М	157'	' [4	m]	NO
	P	MIN	-40M	P-51	М	197'	- ' [5	- m]	YES
	P	PMIN-40MP-6M				236'	-	- m]	NO
	P	PMIN-40MP-8M				315'	<b>' [8</b> 1	m]	NO
	P	MIN	-40M	P-1(	M	393"	[10	m]	YES
	P	MIN	-40M	P-1:	5M	590"	[15	<b>M</b> ]	YES
	P	MIN	-40M	P-20	DM	787"	[20	M]	NO
			λΑΥ Ϝ −ΟΤΓ	requ Ier L	IIRE N ENG	OT BEIN MINIMU THS AV SULT F/	M Ĉ AILA	RDE	ERS
ADM 19/20	24	MENCOM CORPORATION							
JJH 19/20		TITLE: 4 PL MAL PLG PMIN 10AWG							
		size dwg. no. Rev B PMIN-40MP-ZZ C							REV C
		SCALE: 1:1 WEIGHT:						сПЕІ	et 1 OF 1

## DEVICE IS INTENDED TO BE WIRED WITH CONDUCTORS RATED AT 75°C OR HIGHER

D