PIN #	COLOR
1	BLACK
2	GREEN / YELLOW
3	WHITE

DEVICE IS INTENDED TO BE WIRED WITH
CONDUCTORS RATED AT 75°C OR HIGHER



P/N	L	STD?
PMINW-30MP-1M-C011	40" [1m]	YES
PMINW-30MP-2M-C011	79" [2m]	YES
PMINW-30MP-3M-C011	117" [3m]	NO
PMINW-30MP-4M-C011	157" [4m]	NO
PMINW-30MP-5M-C011	197" [5m]	YES
PMINW-30MP-6M-C011	236" [6m]	NO
PMINW-30MP-8M-C011	315" [8m]	NO
PMINW-30MP-10M-C011	393" [10m]	YES
PMINW-30MP-15M-C011	590" [15M]	YES
PMINW-30MP-20M-C011	787" [20M]	NO

PARTS LISTED AS NOT BEING STANDARD
MAY REQUIRE MINIMUM ORDERS
OTHER LENGTHS AVAILABLE,
PLEASE CONSULT FACTORY

MATERIALS	
BODY:	BLACK PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	
STYLE:	TC-ER
AWG:	10 AWG
JACKET:	BLACK TPE
VOLTAGE:	600V
SHIELD:	NO
COUPLING:	NICKEL PLATED BRASS
INSERT:	BLACK PVC
RATINGS	
SCCR RATING:	65 kA Breakers and Fuses
RoHS COMPLIANT:	YES
PROTECTION:	IEC IP67
UL CATEGORY:	PVVA (US), PVVA7 (Canada)
U.S.:	UL 2237 LISTED, File E469485
CANADA:	C-UL 2237 LISTED, File E469485

CAUTION:

RISK OF ELECTRICAL SHOCK
DO NOT DISCONNECT UNDER LOAD

VOLTS	600V
AMPS	42A
TEMP:	-40° to 90°C

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES AND [MM]
MATERIAL
FINISH
DO NOT SCALE DRAWING

DRAWN BY	ADM
DRAWN DATE	02/20/2024
CHECKED BY	JJH
CHECK DATE	02/20/2024

COMMENTS:

MENCOM CORPORATION

TITLE:
3 PL MAL PLG PMIN
10AWG

SIZE	DWG. NO.	REV
B	PMINW-30MP-ZZ-C011	C

SCALE: 1:1 | WEIGHT: | SHEET 1 OF 1