


STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT 6 JACK	CAT 6 JACK

HOUSING MATERIALS		PIC RATINGS/SPECIFICATIONS					
BODY:	EPOXY COATED DIE CAST ALUMINUM						
GASKET:	THERMOPLASTIC ELASTOMER						
HANDLE:	POLYAMIDE						
LEVERS:	STAINLESS STEEL						
OPERATING TEMPERATURE: (-10°C / +60° C (+14° F / +140° F))		NEMA/UL EN 60529:	4, 4X, 12 IP65				
		MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)				
		MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)				
MOUNTING KIT ORDERED SEPARATELY CONTAINS M4x0.7 SS SCREW, NYLON WASHER, SPLIT LOCKWASHER AND M4 NUT P/N: D-PIC-MT		<div></div> <div>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]</div>		MENCOM CORPORATION			
						DRAWN BY	ADM
						DRAWN DATE	07/12/2021
						CHECKED BY	DCG
						CHECK DATE	07/14/2021
<div>PROPRIETARY AND CONFIDENTIAL</div> <div>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.</div>		TITLE: RJ45 X 8; 32					
				COMMENTS:			
						SIZE	DWG. NO.
						B	RJ45-8-32LS
						SCALE: 2:3	
DO NOT SCALE DRAWING							