



The Enclosures ensure IP66 protection rating when mated and locked with the closing levers.

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

Certifications	
(under individual component part numbers)	
US:	UL Recognized
Canada:	C-UL Recognized
Europe:	CE
China:	CCC

MATERIALS			
BODY:		EPOXY COATED DIE CAST ALUMINUM	
GASKET:		THERMOPLASTIC ELASTOMER	
HANDLE:		POLYAMIDE	
LEVERS:		STAINLESS STEEL	
INSERTS:		GLASS REINFORCED THERMOPLASTIC	
CONTACTS:		SILVER PLATED COPPER ALLOY	
DRAWN BY	GO	MENCOM CORPORATION  TITLE:  16 PL ILME KIT	
DRAWN DATE	10/24/2019		
CHECKED BY	ADM		
CHECK DATE	10/24/2019		
COMMENTS:		SIZE DWG. NO. REV	
		B TQDS-16IVA10 A	
		SCALE: 1:2	WEIGHT: SHEET 1 OF 1