



PCB Layout (Ref.)

MATERIAL:

- HOUSING—DSM STANYL TE250F6 (NYLON—46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR, UL94V—0
- CONTACTS—0.35mm THICK PHOS—BRONZE PLATED
WITH HARD GOLD AND TIN/LEAD IN
SOLDER AREA.
- SHIELD—0.25mm THICK COPPER ALLOY,
PLATED WITH NICKEL.

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.

Ordering Information

AJT43L 8 8 8 X-0 X X

Type Positions Contacts Ports Plating
1 = 6u"
3 = 30u"

0 = No Shield
1 = No Tabs
2 = Top Tabs
3 = Side Tabs
4 = Top & Side Tabs

	LED1	LED2		LED1	LED2
1=	Yellow	Green	5=	Green	Red
2=	Green	Green	6=	Red	Green
3=	Green	Yellow	7=	Yellow	Yellow
4=	Green	Orange	8=	Grn/Ylw	Grn/Ylw

Tolerance
unless otherwise specified
mm
.0 ± .25
.00 ± .13
.000 ± .05



P/N: AJT43L888X-0XX

Desc.: Side entry, shielded, LED, thru hole modular jack

Date: 1-26-10
Dimensions in mm

Drawn By: Donna Mears
Verified By: Mike Balekdjian