



PCB LAYOUT
Ref.

MATERIALS:

- HOUSING-DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR,UL94V-0
- CONTACTS-0.35mm THICK PHOS-BRONZE PLATED
WITH HARD GOLD AND GOLD FLASH IN
SOLDER AREA.
- SHIELD-0.25mm THICK COPPER ALLOY,
PLATED WITH NICKEL.

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.

Temperature resistance up to 260°C for 5 seconds.

Ordering Information

AJT34L 8 8 1 X-0 X X

Type Positions Contacts Ports Plating
1 = 6u"
3 = 30u"

Shields
0=No Shield
1=No Tabs
2=Top Tabs
3=Side Tabs
4=Top &
Side Tabs

	LED1	LED2		LED1	LED2
1=	Yellow	Green	5=	Green	Red
2=	Green	Green	6=	Red	Green
3=	Green	Yellow	7=	Yellow	Yellow
4=	Green	Orange	8=	Grn/Ylw	Grn/Ylw
			9=	Red/Grn	Red/Grn

Tolerance
unless otherwise specified
mm
.0 ± .25
.00 ± .13
.000 ± .05



P/N: AJT34L881X-0XX

Desc.: Side entry, shielded, LED, thru hole modular jack

Date: 9-1-09

Dimensions in mm

● = Pin 1